



ANTENNA TECHNOLOGIES LIMITED COMPANY

Model LTEWBSEMTM12F

Key Features

- ✔ Operates from 694 to 3000 MHz, includes LTE, Cellular, Spread Spectrum 902-928 MHz, Cellular, PCS, and WIFI frequencies (single coax)
- ✔ Small footprint, portable and reliable rugged antenna that provides optimum data throughput and wide area coverage
- ✔ 3G, 4G and 5G Broadband Ready



Electrical Specifications	LTEWBSEMTM12F
Frequency Ranges, MHz	694-3000 MHz
Element Type	Edge Slot Radiator
Polarization	Vertical
Peak Gain, dB, min	3 dB
Azimuth Beamwidth	Omni-Directional
Elevation Beamwidth	Cosine
VSWR	2.0:1 (<2.0:1 at resonance points)
Impedance	50 Ω
Cable Type/Length	RG58 Plumin, 12'
Connector	TNC Male
Voltage (GPS)	3/5 Volts

Mechanical Specifications	LTEWBSEMTM12F
Height	1.6" (max)
Diameter	4.62"
Mounting	Side exit magnetic mount
Temperature (Operating/Storage)	-40° to +80° C / -30° to +70°
Radome/Colors Available	ABS Plastic UV/White

22560 Glenn Drive #114 | Sterling, Virginia 20164
www.atlcllc.com sales@atlcllc.com
Office: 703-450-5517

ATLC products for military use may be subject to U.S. ITAR EXPORT CONTROLS, an export license may be required.