

The first edition: September 8, 2009 Revised date: August 6, 2015 Document Number: CPH3225A-031

# SAFETY DATA SHEET (SDS)

# SECTION 1: Product and Company Identification

Product Name Model Name:	Chip type Electric Double Layer Capacitor CPH3225A	
Maximum Use Voltage:	3.3 V	
Capacitance:	0.011 F	
Manufacturer Address:	Seiko Instruments Inc. Micro-Energy Division 45-1, Aza Matsubara, Kamiayashi, Aoba-ku, Sendai-shi, Miyagi, Japan	
Telephone:	+81-22-391-9331 Facsimile: +81-22-391-9330	
Seller Address: Telephone:	Seiko Instruments Inc. Micro-Energy Division Sales Department 8, Nakase 1-chome, Mihama-ku, Chiba-shi, Chiba, Japan +81-43-211-1735 Facsimile: +81-43-211-8034	
Emergency Contact Telephone:	Seiko Instruments Inc. Quality Assurance Department +81-22-391-9331	

# **SECTION 2: Hazards Identification**

GHS Classification	Not applicable
Effects to Human body Possibility of Fire ignition	No data When exposed to fire or extreme heat, it may catch fire, generate heat, leakage or it may burst.

# **SECTION 3: Composition/Information on Ingredients**

Substance/Preparation	Article
Important Note	The capacitor should not be opened or burned, because the following ingredients listed below are contained in it. Its post-discharge or its
	combustion products could be harmful.

## **Materials or Ingredients**

Part Name	Material Name	CAS No.
Anode	Activated carbon	7440-44-0/based material
Cathode	Activated carbon	7440-44-0/based material
Solute	Tetra alkyl ammonium salt	-
Solvent	Hetero-oxide	-
Case	Ceramic	-
Lid	Ni plated metal	-
Seal ring	Au-Ni plated metal	-

#### **SECTION 4: First Aid Measures**

None unless exposed to internal materials. If contents leak, observe the following instructions:

- Inhalation: Fumes can cause respiratory irritation. Ensure the person has fresh air and consult a physician.
- Skin: Immediately wash the skin with plenty of water. If itchiness or irritation due to chemical burns persists, consult a physician.
- Eyes: Immediately rinse the eye with plenty of water.
- Ingestion: If a capacitor is swallowed, consult a physician immediately. If the contents come into contact with the mouth, immediately rinse with of water and consult a physician.

#### **SECTION 5: Fire Fighting Measures**

How to Extinguish Use fire extinguisher or Sand

Keep away the capacitors from the heat source for a fire. Please do not make it to the high temperature to prevent the explosion and the harmful gas being generated.

#### SECTION 6: Accidental Release Measures

N/A (Not Applicable)

#### **SECTION 7: Handling and Storage**

 Handling Do not charge by higher current or higher voltage than specified. Do not reverse placement of (+) and (-). Do not discharge by force. Do not heat, disassemble nor dispose of in fire. In case of leakage or strange smell, keep away from fire to prevent ignition of any leaked electrolyte. Do not use nor leave the capacitors in direct sunlight nor in high-temperature areas. Do not use new and used capacitors together. Do not use different types of capacitors together. If you connect two or more capacitors in series or parallel, please consult us in advance.
Storage Keep capacitors out of children's reach.

Keep capacitors away form direct sunlight, high temperature and humidity.

#### **SECTION 8: Exposure Controls / Personal Protection**

The capacitor is sealed with a metal can in order to avoid leakage of harmful gas or liquid. Follow the instructions in the SECTION 7.

Respiratory Protection:	N/A
Protective Gloves:	N/A
Eye Protection:	N/A
Skin or Body Protection:	N/A

Shape	Chip Capacitor
Chemical System	Activated carbon/ Activated carbon
Rechargeable	YES/ NO

[Chip type Electric Double Layer Capacitor]

# **SECTION 10: Stability and Reactivity**

Stability:StableCondition to Avoid:See section 7Hazardous Mixture:N/AHazardous Decomposition or Byproducts:N/A

### **SECTION 11: Toxicological Information**

N/A

## **SECTION 12: Ecological Information**

N/A

### **SECTION 13: Disposal Considerations**

Dispose of the capacitor in accordance with the respective national, federal, state, and local regulations.

## **SECTION 14: Transport Information**

Energy storage capacity of this capacitor is 0.3Wh, therefore, it is not covered by UN3499 of UN Recommendations on the Transport of Dangerous Goods by Special Provision A186.

### **SECTION 15: Regulatory Information**

N/A

# **SECTION 16: Other Information**

SDS is not applied to products that are used in a sealed condition. So, we do not have the obligation to publish this document since the capacitor corresponds to the condition above. But, we offer this document for reference. The data and evaluation results written on this document was known at the time of preparation, but it is not something that is guaranteed.

End of Documents