
	THE REVISION STATUS OF ALL SHEETS OF THIS DRAWING IS THE SAME AS SHEET 1							
REV	REV DESCRIPTION DATE BY							
А	INITIAL RELEASE	10/28/22	YA					



Dwg. Number	Customer P/N	Times P/N	Length(L) in 'inch'
IE-00417-01	-	IBPS092-SMPMFSMPMF-4.0IN	4 +0.20/-0
IE-00417-02	-	IBPS092-SMPMFSMPMF-6.0IN	6 +0.20/-0
IE-00417-03	-	IBPS092-SMPMFSMPMF-8.0IN	8 +0.20/-0
IE-00417-04	-	IBPS092-SMPMFSMPMF-10.0IN	10 +0.20/-0
IE-00417-05 -		IBPS092-SMPMFSMPMF-12.0IN	12 +0.24/-0

1.0 Scope

This drawing documents the construction and performance of PT- 092 cable assemblies manufactured by Times Microwave systems.

2.0 Cable Information

- 2.1 Cable to be PT-092
- 2.2 Jacket color to be Black
- 2.3 Jacket material to be Tefzel
- 2.4 Nominal cable impedance to be 50 ohms
- 2.5 Cable diameter to be 0.101" [2.57mm] (Nominal).

3.0 Connector Information

3.1 Forward Connector
Type Mini SMP (F) Straight Connector (SP129)

3.2 After Connector

Type Mini SMP (F) Straight Connector (SP129)

Unless otherwise specified, dimensions are in INCH. Tolerances are applicable when specified.	Aŗ	prova	als		F	TIMES MICROWAVE SYSTEMS			
	Drawn	YA	10/28/22				www.timesmicrowave.com		
These drawings and specifications contain proprietary information	Checked			PT-092 CABLE ASSEMBLY					
which is the property of	Approved				(Space Assemblies)				
i imes iviicrowave	Approved			Size	CAGE CODE 68999		Drawing No.: IE-00417-XX		
Systems.				А					
				Scale:	NA	Rev.	(A)	Sheet: 1 of 3	

	THE REVISION STATUS OF ALL SHEETS OF THIS DRAWING IS THE SAME AS SHEET 1								
REV	REV DESCRIPTION DATE BY								
Α	INITIAL RELEASE	10/28/22	YA						

4.0 Electrical Performance

- 4.1 Frequency range: DC 40GHz
- 4.2 Insertion loss & VSWR: As per below table,

Dwg. Number	Max. Insertion Loss in dB	Max. VSWR
Dwg. Number	@ 40GHz	@ 40GHz
IE-00417-01	1.04	1.40
IE-00417-02	1.34	1.40
IE-00417-03	1.63	1.40
IE-00417-04	1.93	1.40
IE-00417-05	2.23	1.40

5.0 Mechanical Performance

- 5.1 Overall Length to be specified length.
- 5.2 Minimum Bend radius is 0.437" [11.1mm].

6.0 Environmental Performance

- 6.1 Installation Temperature Range (-65°C to +150°C)
- 6.2 Storage Temperature Range (-65°C to +150°C)
- 6.3 Operating Temperature Range (-65°C to +150°C)

7.0 Marking

- 7.1 Markers are to be black text on White Color Marker Sleeve.
- 7.2 Marker Configuration to be:

Dwg. Number	Marker 1
IE-00417-01	Times Microwave Systems IBPS092-SMPMFSMPMF-4.0IN \$\$\$\$\$
IE-00417-02	Times Microwave Systems IBPS092-SMPMFSMPMF-6.0IN \$\$\$\$\$
IE-00417-03	Times Microwave Systems IBPS092-SMPMFSMPMF-8.0IN \$\$\$\$\$

Unless otherwise specified, dimensions are in INCH. Tolerances are applicable when specified.	l	prova	als	TIMES MICROWA			/AVE SYSTEMS		
	Drawn	YA	10/28/22		www.timesmicrowave.com			crowave.com	
These drawings and specifications contain proprietary information	Checked			PT-092 CABLE ASSEMBLY					
which is the property of	Approved				(Space Assemblies)				
Times Microwave	Approved			Size	Size CAGE CODE		Drawing No.:		
Systems.				А	68999			-00417-XX	
				Scale:	NA	Rev. ((A)	Sheet: 2 of 3	

	THE REVISION STATUS OF ALL SHEETS OF THIS DRAWING IS THE SAME AS SHEET 1									
REV	REV DESCRIPTION DATE BY									
А	INITIAL RELEASE 10/28/22									

IE-00417-04	Times Microwave Systems IBPS092-SMPMFSMPMF-10.0IN \$\$\$\$\$
IE-00417-05	Times Microwave Systems IBPS092-SMPMFSMPMF-12.0IN \$\$\$\$\$

- 7.3 \$\$\$\$\$ = 5-digit Serial Number for this specific configuration.
- 7.4 Register to be Maintained for Serial Number.

8.0 NOTES

- 8.1 All Dimensions are in INCH.
- 8.2 Assemblies built in Class 100,000 clean room.
- 8.3 Low outgassing materials per ASTM E595.
- 8.4 Unless Otherwise Specified: Tolerance will be,

Linear Dimension	Tolerance
<20 INCH	±0.4 INCH
20-79 INCH	±0.6 INCH
>79 INCH	±0.8 INCH

^{**}Tolerances are not accumulative.

Unless otherwise specified, dimensions are in INCH. Tolerances are applicable when specified.	Aŗ	prova	als	_	F	TIMES MICROWAVE SYSTEMS		
	Drawn	YA	10/28/22		www.timesmicrowave.com			
These drawings and specifications contain proprietary information	Checked			PT-092 CABLE ASSEMBLY				
which is the property of	Approved				(Space Assemblies)			
i imes iviicrowave	Approved			Size	CAGE CODE 68999		Drawing No.: IE-00417-XX	
Systems.				Α				
				Scale:	NA	Rev. ((A)	Sheet: 3 of 3