

Product Specifications

Nanosecond

ExtremeSlim HDMI Cable - Mini to Mini HDMI (2.6 FT / 0.8 m)

World's thinnest & most flexible 4K Mini HDM to Mini HDMI cable. Strong and flexible, allowing connections in tight spaces.







MODEL NUMBER: RDNC-C60BK Product Highlights / Features

World's Thinnest & Most Flexible Cable

World's thinnest & most flexible HDMI Cable. Strong and flexible, allowing connection in tight spaces.

4K Ultra HD HDMI

Incredibly thin and capable of delivering the maximum high-definition digital video and multi-channel digital audio performance. Supports 4K Ultra High-Definition HDMI and HDR.

0.8m Mini HDMI to Mini HDMI Cable

The perfect cable for streaming 4K HDR video from Apple TV, MacBook, iPhone, smartphones, tablets, PC laptops, cameras, drones, and all HDMI video devices.

Perfect Connection

24k gold contacts for signal integrity.

Premium Quality

Official Certified HDMI adopter cord carries the official Premium High Speed HDMI Signal.



Product Specifications

OVERVIEW	
Part Number	RDNC-C60BK
Product Type	Passive
Technology	HDMI
VIDEO	
Max Supported Video Resolution	4K @ 60 Hz
INPUT	
Production Length (in.)	31.5
Production Length (ft.)	2.6
PHYSICAL	
Color	Black
Cable Jacket Material	PVC
Cable Outer Diameter (O.D)	2mm
Cable Length	2.6 ft / 0.8 meter
Cable Length (m.)	0.8
Cable Length (in.)	31.5
Material of Construction	PVC
Wire (AWG)	40
Cable Type	Micro-Coaxial
CONNECTIONS	
Side A – Connector 1	Mini HDMI (MALE)
Side B – Connector 1	Mini HDMI (MALE)
Connector Plating	Gold
Contact Plating	Gold
STANDARDS & COMPLIANCE	
Compliance	RoHS
WARRANTY	
Product Warranty Period	3 Years Limited Warranty

© 2022 Nanosecond LLC

This document contains proprietary & confidential information belonging exclusively to Nanosecond. All information is subject to change without notice and should not be construed as a commitment by Nanosecond LLC. Nanosecond assume no responsibility for any errors that may appear in this specification. In no event shall Nanosecond be liable for incidental or consequential damages arising from use of this specification/products. All Rights Reserved.