

UNO-2362G

AMD® Dual Core T40E Small-Size Automation Computer w/ 1 x GbE, 1 x mPCIe, HDMI, DP

NEW



Features

- Onboard AMD® Dual Core T40E 1.0GHz processors with 2GB DDR3 SODIMM memory
- 1 x GbE, 4 x USB 2.0, 1 x RS-232, 1 x RS-485, 1 x DP, 1 x HDMI
- Compact with fanless design
- Rubber stopper design with captive screws
- Daisy-chain for Ethernet with auto-bypass protection enabled
- Diverse system I/O and isolated digital I/O by iDoor technology
- 3G/GPS/GPRS/Wi-Fi communication by iDoor technology
- Supports battery-backup MRAM by iDoor technology
- Chassis grounding protection

Introduction

Advantech's UNO-2000 series of Embedded Automation Computers are fanless, with a highly ruggedized embedded operating system (Windows CE, Windows XPE, Linux-Embedded). The series also includes iDoor technology which supports automation feature extensions such as industry fieldbus communication, Wi-Fi/3G, Digital I/O, including palm, small, and regular-size form-factors with indicated market segments in terms of entry, value and performance product positioning. Both entry and value Embedded Automation Computers feature specific functions and they are suitable for data gateway, concentrator and data server applications. The performance model can shorten your development time and offer multiple networking interfaces to fulfill a diverse range of requirements.

Specifications

General

- Certification** CE, FCC, UL, CCC, BSMI
- Dimensions (W x D x H)** 190 x 107 x 47 mm (7.5" x 4.2" x 1.8")
- Form Factor** Small Size
- Enclosure** Aluminum Housing
- Mounting** Stand, Wall, DIN-rail (Optional), VESA (Optional)
- Weight (Net)** 1.0kg (2.2lbs)
- Power Requirement** 24VDC ±15%
- Power Consumption** 14W (Typical), 47.3W (Max)
- OS Support** Microsoft® Windows XP/7/8 WES7
Advantech Linux

System Hardware

- BIOS** AMI UEFI 32Mbit Flash BIOS
- Watchdog Timer** Programmable 255 levels timer interval, from 1 to 255 sec
- Processor** AMD® G-series T40E 1.0GHz dual core
- System Chip** AMD® A50M FCH
- Memory** On-board 2GB DDR3 1066 MHz
- Graphics Engine** AMD Radeon™ HD 6250 DirectX® 11 graphics with UVD 3.0 2D/3D Accelerator
- Ethernet** Realtek RTL8111E, Marvell 88E6172 Giga Ethernet switch with daisy chain technology
- LED Indicators** LEDs for Power, battery, LAN (Active, Status) and HDD
- Storage** One mSATA drive
One drive bay for SATA 2.5" HDD (Compatible with 9.5mm height HDD)
Note: iDoor technology isn't compatible with HDD storage
- Expansion** 1 x Full-size mPCIe slot, mPCIe 2.0 (supports SIM card)

I/O Interfaces


- Serial Ports** 1 x RS-232, DB9, 50 ~ 115.2kbps
1 x RS-485, DB9, auto flow control, 50 ~ 115.2kbps
- LAN Ports** 2 x RJ45, 10/100/1000 Mbps IEEE 802.3u 1000BASE-T Fast Ethernet
- USB Ports** 4 x USB 2.0 Compliant
- Displays** 1 x DisplayPort 1.1, supports 1920 x 1080 @ 60Hz
1 x HDMI v1.3, supports 1920 x 1080 @ 60Hz
- Power Connector** 1 x 2 Pins, Terminal Block
- Grounding Protection** Chassis Grounding

Environment


- Operating Temperature** - 10 ~ 60°C (14 ~ 140°F) @ 5 ~ 85% RH with 0.7m/s airflow
- Storage Temperature** - 40 ~ 85°C (-40 ~ 185°F)
- Relative Humidity** 10 ~ 95% RH @ 40°C, non-condensing
- Shock Protection** Operating, IEC 60068-2-27, 50G, half sine, 11ms
- Vibration Protection** Operating, IEC 60068-2-64, 2Grms, random, 5 ~ 500Hz, 1hr/axis (mSATA)
Operating, IEC 60068-2-64, 0.75Grms, random, 5 ~ 500Hz, 1hr/axis (HDD)
- Ingress Protection** IP40

Installation Scenario

DIN-rail Mount Illustration




VESA Mount Illustration




Dimensions


Unit: mm



Front I/O View



Rear I/O View



Ordering Information

- UNO-2362G-T2AE** AMD G-series T40E 1.0GHz, 2GB, 1 x GbE, 1 x mPCIe, HDMI, DP

iDoor Modules

- PCM-24D2R2-BE** 2-Port Isolated RS-232 mPCIe, DB9
- PCM-24D2R4-BE** 2-Port Isolated RS-422/485 mPCIe, DB9
- PCM-24D4R2-BE** 4-Port Non-Isolated RS-232 mPCIe, DB37
- PCM-24D4R4-BE** 4-Port Non-Isolated RS-422/485 mPCIe, DB37
- PCM-26D2CA-AE** 2-Port Isolated CANBus mPCIe, CANopen, DB9
- PCM-27D24DI-AE** 24-Channel Isolated Digital I/O w/ counter mPCIe, DB37
- PCM-24R1TP-AE** 1-Port Gigabit Ethernet, Intel® 82574L, mPCIe, RJ45
- PCM-24S2WF-BE** WiFi 802.11 ac/a/b/g/n 2T2R w/Bluetooth 4.1
- PCM-24S33G-AE** Wide-Temp 3.75G HSPA and GPS, 2-in-1, Full-size mPCIe w/ Redundant SIM Card holder, 2-port SMA

Optional Accessories

- 96PSA-A60W24T2** 60W AC to DC UNO series power adapter (Industrial Grade)
- 1702002600** Power Cable US Plug 1.8 M (Industrial Grade)
- 1702002605** Power Cable EU Plug 1.8 M (Industrial Grade)
- 1702031801** Power Cable UK Plug 1.8 M (Industrial Grade)
- 1700000596** Power Cable China/Australia Plug 1.8 M (Industrial Grade)
- UNO-2000G-DMKAE** UNO-2000 DIN Rail Kit
- UNO-2000G-VMKAE** UNO-2000 VESA Mount Kit

Embedded O/S

- 2070014506** Win10 LTSB X64 MUI. V6.00B002 image
- 2070013078** WEC7 MUI.V4.00 B022 image
- 2070015121** WES2009 x86 MUI v3.35 B001 image

Please note: If some optional modules are offered with the system, additional system certificates may be required in certain regions/countries. Please contact Advantech for certificate compliance.