

# TRAYCONTROL® 600

flexible, oil resistant, open installation TC-ER, PLTC-ER, ITC-ER, NFPA 79



## Technical data

- PVC power cable acc. to UL Std.1277 and UL Std.2277
- **Temperature range**  
UL/CSA TC -40°C to +90°C  
UL/AWM -40°C to +90°C
- **Nominal voltage**  
TC 600 V  
AWM 1000 V  
WTTTC 1000 V
- **Test voltage**  
3000 V
- **Minimum bending radius**  
5x cable Ø
- **Insulation resistance**  
min. 20 MOhm x km
- **Radiation resistance**  
up to 80x10<sup>6</sup> cJ/kg (up to 80 Mrad)

## Cable structure

- Bare copper conductor, fine wire with AWG dimensions
- Core insulation of special PVC with transparent nylon skin
- Core identification to DIN VDE 0293 black cores with continuous white numbering
- GN-YE conductor, 3 cores and above in the outer layer
- Cores stranded in layers with optimal lay length
- Separator
- Outer sheath of special PVC
- Sheath colour: black (RAL 9005)
- With length marking in feet

## Properties

- The materials used during manufacturing are cadmium-free, contain no silicone and are free from substances harmful to the wetting properties of lacquers
- UV resistant
- **Tests**
- Self-extinguishing and flame retardant acc. to CSA FT4
- **UL:**  
TC-ER, PLTC-ER (AWG 18 - AWG 12), ITC-ER (AWG 18 - AWG 12), UL Type WTTTC, UL Type MTW, NFPA 79, Oil Res I (Oil Res II also available), 90° C dry / 75° C wet, Class 1 Div. 2 per NEC Art. 336, 392, 501
- **CSA:**  
c(UL) CIC-TC FT4, CSA AWM I/II A/B FT4

## Note

### Advantages

- TC-ER, Tray Cable Exposed Run
- Simple installation
- Outstanding flexibility

## Application

NFPA 79 conformant flexible power cable up to 600 V (WTTTC 1000 V), for all machinery in plant construction. Suitable for installation in dry, humid and damp environments, outdoors and pipes. For underground installation and for open, unprotected installation from the cable rack to machines in industrial plants.

CE = Product conforms with Low-Voltage Directive 2014/35/EU.

Part no.	Cross-section mm <sup>2</sup>	No. cores x AWG-No.	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km
62020	0,507	2 x 20	6,6	9,8	60,0
62021	0,507	3 x 20	7,0	14,6	64,0
62022	0,507	4 x 20	7,5	19,5	79,0
62023	0,507	5 x 20	8,1	24,4	92,0
62024	0,507	7 x 20	8,7	34,1	124,0
62025	0,507	9 x 20	9,8	43,8	210,0
62026	0,507	12 x 20	10,1	58,4	263,0
62027	0,507	18 x 20	12,9	87,6	305,0
62028	0,507	25 x 20	15,7	121,7	371,0
62902	0,963	2 x 18	7,3	18,5	68,0
62903	0,963	3 x 18	7,6	27,8	68,0
62904	0,963	4 x 18	8,2	37,0	97,0
62905	0,963	5 x 18	8,9	46,3	116,0
62906	0,963	7 x 18	9,6	64,8	147,0
62907	0,963	9 x 18	11,0	83,2	186,0
62908	0,963	10 x 18	11,6	92,5	199,0
62909	0,963	12 x 18	12,2	111,0	250,0
62910	0,963	15 x 18	13,5	138,7	292,0
62911	0,963	16 x 18	13,6	147,9	306,0
62912	0,963	18 x 18	15,0	166,4	365,0
62913	0,963	19 x 18	15,1	175,7	384,0
62914	0,963	25 x 18	17,4	231,2	480,0
62915	0,963	27 x 18	17,7	249,6	521,0
62916	0,963	34 x 18	19,7	314,4	625,0
62917	0,963	37 x 18	20,1	342,0	684,0
62918	0,963	41 x 18	21,0	379,0	744,0
62919	0,963	50 x 18	24,0	462,3	933,0
62920	0,963	61 x 18	25,2	564,0	1095,0
62921	1,31	2 x 16	7,8	25,2	80,0
62922	1,31	3 x 16	8,2	37,8	86,0

Part no.	Cross-section mm <sup>2</sup>	No. cores x AWG-No.	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km
62923	1,31	4 x 16	8,8	50,3	120,0
62924	1,31	5 x 16	9,6	62,9	130,0
62925	1,31	6 x 16	10,2	75,5	164,0
62926	1,31	7 x 16	10,5	88,0	188,0
62927	1,31	8 x 16	11,1	100,7	201,0
62928	1,31	9 x 16	12,0	113,2	238,0
62929	1,31	10 x 16	12,4	125,8	259,0
62930	1,31	12 x 16	13,6	151,0	301,0
62931	1,31	14 x 16	14,5	176,1	356,0
62932	1,31	15 x 16	15,2	188,7	379,0
62933	1,31	16 x 16	16,0	201,3	405,0
62934	1,31	18 x 16	16,4	226,4	430,0
62935	1,31	19 x 16	16,6	239,0	450,0
62936	1,31	20 x 16	17,2	251,6	481,0
62937	1,31	25 x 16	18,9	314,5	564,0
62938	1,31	27 x 16	19,3	339,6	629,0
62939	1,31	30 x 16	20,0	377,3	701,0
62940	1,31	34 x 16	22,5	427,6	775,0
62941	1,31	40 x 16	23,5	503,1	946,0
62942	1,31	41 x 16	24,0	515,7	967,0
62943	1,31	50 x 16	26,1	628,8	1137,0
62944	1,31	61 x 16	27,5	767,2	1345,0
62945	2,08	2 x 14	8,9	40,0	100,0
62946	2,08	3 x 14	9,2	60,0	117,0
62947	2,08	4 x 14	10,1	80,0	141,0
62948	2,08	5 x 14	10,9	100,0	152,0
62949	2,08	6 x 14	11,5	120,0	216,0
62950	2,08	7 x 14	12,0	140,0	255,0
62951	2,08	9 x 14	14,7	180,0	312,0
62952	2,08	10 x 14	15,8	200,0	378,0

Continuation ▶

# TRAYCONTROL® 600

flexible, oil resistant, open installation TC-ER, PLTC-ER, ITC-ER, NFPA 79



Part no.	Cross-section mm²	No. cores x AWG-No.	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km
62953	2,08	12 x 14	16,4	240,0	434,0
62954	2,08	16 x 14	18,0	320,0	550,0
62955	2,08	18 x 14	18,9	359,0	616,0
62956	2,08	19 x 14	19,0	380,0	634,0
62957	2,08	25 x 14	23,0	500,0	817,0
62958	3,31	2 x 12	9,7	63,0	132,0
62959	3,31	3 x 12	10,2	95,0	177,0
62960	3,31	4 x 12	11,2	127,0	201,0
62961	3,31	5 x 12	12,3	159,0	274,0
62962	3,31	6 x 12	13,6	191,0	315,0
62963	3,31	7 x 12	13,9	222,0	353,0
62964	3,31	9 x 12	16,4	286,0	476,0
62965	3,31	12 x 12	18,3	381,0	613,0
62966	3,31	16 x 12	19,8	508,0	783,0
62967	3,31	19 x 12	22,3	604,0	918,0
62968	3,31	20 x 12	23,1	636,0	916,0
62969	3,31	25 x 12	25,8	794,0	1286,0
62970	5,26	2 x 10	12,2	101,0	213,0
62971	5,26	3 x 10	12,9	151,5	283,0
62972	5,26	4 x 10	15,0	202,0	387,0
62973	5,26	5 x 10	16,3	252,5	473,0
62974	5,26	7 x 10	17,7	353,5	607,0

Part no.	Cross-section mm²	No. cores x AWG-No.	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km
62975	5,26	9 x 10	20,6	454,5	771,0
62976	5,26	12 x 10	24,1	606,0	1061,0
62977	5,26	19 x 10	27,2	959,5	1528,0
62978	8,37	4 x 8	19,2	321,4	615,0
62979	8,37	5 x 8	21,0	401,8	768,0
62980	13,3	3 x 6	19,5	383,1	700,0
62981	13,3	4 x 6	22,4	510,7	907,0
62982	13,3	5 x 6	24,5	638,4	1100,0
62983	21,2	3 x 4	24,4	610,6	1061,0
62984	21,2	4 x 4	27,0	814,1	1366,0
62985	21,2	5 x 4	29,9	1017,6	1631,0
62986	33,6	3 x 2	28,2	967,7	1480,0
62987	33,6	4 x 2	31,4	1290,3	1922,0
62988	33,6	5 x 2	34,6	1612,8	2360,0
62989	42,3	4 x 1	35,6	1624,0	2397,0
62990	52,9	4 x 1/0	38,7	2031,0	2938,0
62991	67,3	4 x 2/0	42,1	2584,0	3569,0
62992	84,4	4 x 3/0	49,4	3256,0	4181,0
62993	106,7	4 x 4/0	52,0	4097,0	5747,0
62994	128,4	4 x 250 kcmil	55,8	4931,0	7591,0
62995	181,9	4 x 350 kcmil	64,3	6985,0	8299,0
62996	257,6	4 x 500 kcmil	74,1	9892,0	11549,0

Dimensions and specifications may be changed without prior notice. (RN01)