

BRUSH MOTORS

The power of silence



ABOUT CROUZET

The Motion product line provides innovative engineering expertise, high quality service and a complete offer of standard direct drives, geared motors and motion control solutions for applications where performance is key. Our ability to customize solutions as per virtually any customers' request makes us the right partner to tackle the most demanding projects.

Crouzet is a brand of InnoVista Sensors™.

With a long-term commitment to technological excellence, the engineering teams have mastered the following core technologies and know-how:

- › Electromagnetism
- › Thermal dynamics
- › Electromechanical systems
- › Electronic drives

Covering the power range from 1 to 1000 W peak (1/100 to 1HP+) and available with spur, worm or planetary gearboxes, plus adapted controllers, our offer is specifically designed for access control systems, pumps and valves, railway applications, electrical equipment, medical equipment and the industry.

INNOVISTA SENSORS

InnoVista Sensors™ is a worldwide industrial specialist of sensors, controllers and actuators for automated systems.

Through its brands, Crouzet and Systron Donner Inertial, InnoVista Sensors™ offers a wide range of reliable, efficient and customizable components dedicated to the Aerospace & Defense, Transportation and Industrial markets and segments.

Thanks to the recognized expertise of its teams and a strong innovation policy, InnoVista Sensors™ brings performance enhancing solutions to its customers worldwide.

InnoVista Sensors™: your trusted partner of choice to face industrial challenges of today and tomorrow.

www.innovistasensors.com


Designs & Manufactures



Sensors



Controls



Actuators

For



Aerospace
& Defense



Transportation




Industry

ADAPTATION WHEEL

To meet market expectations and provide customers with the right solutions within the shortest timeframes, Crouzet has structured its processes around the different types of product available: standard products, adapted products or products specially developed for a customer.

Introducing the adaptation wheel...



1 STANDARD PRODUCTS

Sales service

A full range of motors, geared motors and associated controllers. You can create your automation control applications as quickly as possible

2 PRODUCTS WITH ADDED VALUE

Customer Adaptation Centre

All our standard products can have additional factory-mounted auxiliaries or accessories: connectors, leads, special terminals, customized shafts, adaptor plates, etc. Seamless integration in your equipment means you benefit from simpler logistics and optimum installation reliability.

3 ADAPTED PRODUCTS

Customer Adaptation Centre

Defined in coordination between your project teams and our specialists, these adapted products have exactly the right levels of performance and functionality you need for your applications.

4 SPECIAL PRODUCTS

Engineers and teams Dedicated project

From the very start of a project, Crouzet' experts work closely with your teams to develop the specification. All our design, industrialization and approval expertise goes into developing Motion Control solutions that are tailored to your requirements.

DCmind BRUSH

THE QUIETEST ON THE MARKET

With more than 50 years' experience, Crouzet, a specialist in customized Motion Solutions, presents its DCmind Brush range of direct current Brush motors.

Designed by the engineers in Crouzet, this range - the quietest on the market - is ideally suited to the medical, industrial and commercial equipment sectors.

PRODUCT BENEFITS:

- > Exceptionally quiet: 35 dBA
- > Service life up to 24,000 hours
- > More than 80% efficiency
- > Output power up to 104 W
- > 12, 24, 48, 90 and 120 V_{DC} power supplies and other voltages on request
- > Up to IP69K
- > Conformity to the specific standards for your market and required approvals

EXCEPTIONALLY QUIET

- Systematic approach to eliminate noise
 - > At source
 - > From transmission
 - > From dispersion

Innovative design

- > Choice of new materials
- > Optimization of component assembly (centering, perpendicularity, parallelism, etc.)

A range of gearbox

- > In line with high performance motor

SERVICE LIFE UP TO 24,000 HOURS


- > Its average service life, in continuous duty, is between 24,000 hours at no-load and 5000 hours at rated load

MORE THAN 80% EFFICIENCY

- High performance magnetic circuit
 - > Optimum magnetic flux
 - > Magnets designed to optimize the detent torque

Optimal electromagnetic performance

- > Energy losses on the winding
- > Magnetic losses
- > Minimal friction



The **Crouzet DCmind Brush Motor Series** has earned the honor of 2013 Readers' Choice **Product of the Year** Winner by Medical Design Briefs magazine. Every year the editors of the magazine review new products and choose the best of the best for voting by their readership in the annual awards competition. The Crouzet DCmind Brush Motor Series was chosen by editors for its outstanding technical merit and practical value.

**MEDICAL
DESIGN BRIEFS**
2013 Product of the Year

EXCEPTIONAL PERFORMANCE EVEN IN SEVERE ENVIRONMENTS

- IP65 as standard
 - > Front and rear end caps redesigned to ensure a good seal, including wire exits
 - > IP 67 on request
 - > IP 69K on request

Approvals and conformities

- > UL 1004 - CE - ROHS
- > Medical (IEC 60601-1)
- > Office automation (IEC 60950)
- > Household appliances (IEC 60335)

DCmind BRUSH: ECO-DESIGN

Crouzet has been involved in eco-design for many years (ISO 14001 held since 1997).

Its production plants have some of the lowest existing impacts on the environment, and in addition, all Crouzet's product developments are constantly reducing their footprint on ecosystems.

The DCmind Brush motors range reduces this footprint to a third of more conventional manufacturing techniques.

ECOLOGICAL FOOTPRINT ON NATURAL ENVIRONMENTS:


Throughout a product's service life, from design through to the recycling stage, every manufactured product has an impact on ecosystems.

Reducing this footprint is a priority for any company that cares about the environment.

The diagram opposite compares the footprint of a conventional design with the new design.




NOISE LEVEL:
A noise level comparable to the sound of the wind rustling in the trees...



Footprint usually left on ecological environments by standard industrial design motors.













The new Crouzet design's ecological footprint.



DCmind BRUSH: SELECTION GUIDE

To complement the current range from Crouzet, the latest generation of DC Brush direct drive and geared motors have been precision engineered to minimise all mechanical and electro-mechanical variations.

Extremely quiet, this range is ideally suited to medical and laboratory applications.

	OUTPUT POWER (W)	NOMINAL TORQUE (mNm)	NOMINAL SPEED (rpm)	TYPE OF GEARBOX		PLANETARY Ø 42	PLANETARY Ø 52	90°
				FAMILY	MAX. TORQUE (Nm)			
DIRECT DRIVE MOTORS								
Ø 42 mm								
	15	50	2920					
	24	75	3100					
	35	110	3000					
Ø 63 mm								
	57	180	3000					
	104	290	3430					

Motors 24 VDC

x = 1: IP65 | x = 5: brake | x = 9: encoder
y = 0: IP65 | y = 5: brake | y = 9: encoder

ACCESSORIES AND ADAPTATIONS

- > Rear Friction Brake
- > 1,000 Pulse 2-Channel Encoder
- > Connectors
- > Voltage, speed, power
- > Shaft dimensions and material
- > Motor length
- > Other ratios and gearboxes
- > Etc.

NEW ADAPTATION POSSIBILITIES

- > Railway application (compliance with fire/smoke regulations)
- > Isolation for use at 230 V
- > Other colours



DCmind: DC DIRECT-DRIVE BRUSH MOTORS

Ø 42 mm - 20 W



- > Silent motor
- > 12 V and 24 V built in EMC filter class B
- > Excellent efficiency
- > Long life
- > IP65
- > In accordance with UL - CE - ROHS regulations

Part numbers

	12 V	24 V	48 V
Type	89810	89810	89810
Voltage	12 V~	24 V~	48 V~
References	89810007 89810507 89810907	89810003 89810503 89810903	89810008 89810508 89810908
Option: IP65 level			
Option: holding brake 0.25 Nm, 24 V~			
Option: 2 channels encoder 1000 pulses/revolution, 5 V~			
No-load characteristics			
Speed (rpm)	4200	4000	4100
Absorbed current (A)	0.26	0.11	0.07
Nominal characteristics			
Speed (rpm)	2900	2920	2980
Torque (mNm)	50	50	50
Output power (W)	15	15	16
Absorbed current (A)	2.1	0.53	0.53
Efficiency (%)	60	64	61
Maximum efficiency characteristics			
Speed (rpm)	3500	3500	3400
Torque (mNm)	27	30	31
Output power (W)	10	10	11
Absorbed current (A)	1.26	0.6	0.35
Efficiency (%)	65	72	65
General characteristics	Class E	Class E	Class E
Insulation conforming to IEC60085			
Noise level (dBA)	17	35	35
Max. output power (W)	158	20	19
Starting torque (mNm)	6.1	3.3	180
Starting current (A)	2	1.7	1.7
Resistance (Ω)	2	7.3	28
Inductance (mH)	1.3	6	22
Torque constant (mNm/A)	27	56	109
Electrical time constant (ms)	0.7	0.8	0.8
Mechanical time constant (ms)	20	17	18
Inertia (g.cm ²)	75	75	75
Weight (g)	340	340	340
Commutator segments	8	8	8
Service life (h)	4000	4000	4000
Wires length (mm)	200	200	200
Ball bearing	✓	✓	✓
Comments			
IP65 level except for the output shaft. Encoder and brake options are IP20.			

Product adaptations, contact us




- > Special output shaft
- > Shaft with pinion, pulley, worm gear
- > Special supply voltage
- > Other wire length
- > Optical or Hall effect encoder - 1 or 2 channels
- > Specific motor mounting flange
- > Special motor connectors
- > IP67, IP69K


Product made to order

Curves


89810007 - 89810507 - 89810907




89810008 - 89810508 - 89810908



89810003 - 89810503 - 89810903




Dimensions (mm)



- 1 2 x M3 at 180° depth 5 over Ø 32
- 2 2 x Ø 2.75 at 120° depth 5 over Ø 32

Options

Holding brake 0.25 Nm



DCmind: DC DIRECT-DRIVE BRUSH MOTORS

Ø 42 mm - 36 W



- > Silent motor
- > 12 V and 24 V built in EMC filter class B
- > Excellent efficiency
- > Long life
- > IP65
- > In accordance with UL - CE - ROHS regulations

Part numbers

Type	12 V	24 V	48 V
Voltage	89800 12 V***	89800 24 V***	89800 48 V***
References			
Option: IP65 level	89800007	89800008	89800003
Option: holding brake 0,25 Nm, 24 V***	89800507	89800508	89800503
Option: 2 channels encoder 1000 pulses/revolution, 5 V***	89800907	89800908	89800903
No-load characteristics			
Speed (rpm)	4200	4000	3930
Absorbed current (A)	0,26	0,115	0,07
Nominal characteristics			
Speed (rpm)	3050	3100	3150
Torque (mNm)	75	75	75
Output power (W)	24	24	25
Absorbed current (A)	3	1,43	0,72
Efficiency (%)	67	71	72
Maximum efficiency characteristics			
Speed (rpm)	3620	3500	3450
Torque (mNm)	38	41	48
Output power (W)	14	15	17
Absorbed current (A)	1,6	0,84	0,49
Efficiency (%)	73	75	74
General characteristics			
Insulation conforming to IEC60085	Class E	Class E	Class E
Noise level (dBA)	35	35	35
Max. output power (W)	30	36	39
Starting torque (mNm)	276	344	377
Starting current (A)	10,3	6,1	3,3
Resistance (Ω)	1,2	3,9	14,5
Inductance (mH)	0,8	3	13
Torque constant (mNm/A)	27	57	115
Electrical time constant (ms)	0,7	0,8	0,9
Mechanical time constant (ms)	17	13	12
Inertia (g.cm ²)	110	110	110
Weight (g)	450	450	450
Commutator segments	8	8	8
Service life (h)	4000	4000	4000
Wires length (mm)	200	200	200
Ball bearing	✓	✓	✓
Comments			
IP65 level except for the output shaft. Encoder and brake options are IP20.			

Product adaptations, contact us




- > Special output shaft
- > Shaft with pinion, pulley, worm gear
- > Special supply voltage
- > Other wire length
- > Optical or Hall effect encoder - 1 or 2 channels
- > Specific motor mounting flange
- > Special motor connectors
- > IP67, IP69K


Product made to order

Curves


89800007 - 89800507 - 89800907




89800008 - 89800508 - 89800908



89800003 - 89800503 - 89800903




Dimensions (mm)




- 1 2 x M3 at 180° depth 5 over Ø 32
- 2 2 x Ø 2,75 at 120° depth 5 over Ø 32

Options

Holding brake 0,25 Nm



Encoder



DCmind: DC DIRECT-DRIVE BRUSH MOTORS

Ø 42 mm - 51 W



- > Silent motor
- > 12 V and 24 V built in EMC filter class B
- > Excellent efficiency
- > Long life
- > IP65
- > In accordance with UL - CE - ROHS regulations

Part numbers

	12 V	24 V	48 V
Type	89850	89850	89850
Voltage	12 V	24 V	48 V
References	89850007 89850507 89850907	89850008 89850508 89850908	89850003 89850503 89850903
Option: IP65 level			
Option: holding brake 0.25 Nm, 24 V			
Option: 2 channels encoder 1000 pulses/revolution, 5 V			
No-load characteristics			
Speed (rpm)	4000	3750	3840
Absorbed current (A)	0.31	0.14	0.08
Nominal characteristics			
Speed (rpm)	3000	3000	3000
Torque (mNm)	110	110	110
Output power (W)	35	35	35
Absorbed current (A)	4.1	1.9	1
Efficiency (%)	70	76	72
Maximum efficiency characteristics			
Speed (rpm)	3500	3320	3400
Torque (mNm)	52	60	60
Output power (W)	19	21	21
Absorbed current (A)	2.1	1.1	0.58
Efficiency (%)	76	80	77
General characteristics			
Insulation conforming to IEC60085	Class E	Class E	Class E
Noise level (dBA)	35	35	35
Max. output power (W)	44	51	50
Starting torque (mNm)	420	520	500
Starting current (A)	15	8.4	4.2
Resistance (Ω)	0.8	2.9	11.4
Inductance (mH)	0.5	2	8
Torque constant (mNm/A)	29	63	120
Electrical time constant (ms)	0.6	0.7	0.7
Mechanical time constant (ms)	15	12	13
Inertia (g.cm ²)	160	160	160
Weight (g)	620	620	620
Commutator segments	8	8	8
Service life (h)	4000	4000	4000
Wires length (mm)	200	200	200
Ball bearing	✓	✓	✓
Comments			
IP65 level except for the output shaft. Encoder and brake options are IP20.			

Product adaptations, contact us




- > Special output shaft
- > Shaft with pinion, pulley, worm gear
- > Special supply voltage
- > Other wire length
- > Optical or Hall effect encoder - 1 or 2 channels
- > Specific motor mounting flange
- > Special motor connectors
- > IP67, IP69K


Product made to order

Curves


89850007 - 89850507 - 89850907




89850008 - 89850508 - 89850908



89850003 - 89850503 - 89850903




Dimensions (mm)



- 1 2 x M3 at 180° depth 5 over Ø 32
- 2 2 x Ø 2.75 at 120° depth 5 over Ø 32

Options

Holding brake 0.25 Nm



Encoder

DCmind: DC DIRECT-DRIVE BRUSH MOTORS

Ø 63 mm - 102 W



- > Silent motor
- > 12 V and 24 V built in EMC filter class B
- > Excellent efficiency
- > Long life
- > IP65
- > In accordance with UL - CE - ROHS regulations

Part numbers

	12 V	24 V	48 V	90 V
Type	89630	89630	89630	89630
Voltage	12 V	24 V	48 V	90 V
References	89630011 89630511 89630911	89630012 89630512 89630912	89630003 89630503 89630903	89630004 89630504 89630904
Option:	holding brake 0.5 Nm, 24 V			
Option:	2 channels encoder 1000 pulses/revolution, 5 V			
No-load characteristics	3830 0.52	3600 0.23	3550 0.14	3550 0.07
Speed (rpm)				
Absorbed current (A)				
Nominal characteristics	2850	3000	3050	3000
Speed (rpm)	180	180	180	180
Torque (mNm)	54	57	57	57
Output power (W)	6.5	3.1	1.54	0.83
Absorbed current (A)	69	77	78	76
Efficiency (%)				
Maximum efficiency characteristics	3240	3240	3200	3200
Speed (rpm)	90	111	131	128
Torque (mNm)	31	38	44	43
Output power (W)	3.5	1.97	1.15	0.61
Absorbed current (A)	75	80	80	78
Efficiency (%)				
General characteristics	Class E	Class E	Class E	Class E
Insulation conforming to IEC 60085	35	35	35	35
Noise level (dBA)	70	102	114	109
Max. output power (W)	703	1090	1230	1177
Starting torque (mNm)	24	17.2	9.7	5
Starting current (A)	0.5	1.4	4.9	18
Resistance (Ω)	0.38	1.7	7	25
Inductance (mH)	30	64	129	237
Torque constant (mNm/A)	0.8	1.2	1.4	1.4
Electrical time constant (ms)	21	13	11	12
Mechanical time constant (ms)	380	380	380	380
Inertia (g.cm²)	1200	1200	1200	1200
Weight (g)	12	12	12	12
Commutator segments	5000	5000	5000	5000
Service life (h)	200	200	200	200
Wires length (mm)				
Ball bearing				
Comments				
IP65 level except for the output shaft. Encoder and brake options are IP20.				


Product adaptations, contact us




- > Special output shaft
- > Shaft with pinion, pulley, worm gear
- > Special supply voltage
- > Other wire length
- > Optical or Hall effect encoder - 1 or 2 channels
- > Specific motor mounting flange
- > Special motor connectors
- > IP67, IP69K

Product made to order

Curves



Dimensions (mm)




- 1 4 x M5 at 90° depth 10 over Ø 40
- 2 4 x Ø 3.65 at 90° depth 8 over Ø 48
- 3 4 x M5 at 90° depth 7 over Ø 40

Options

Holding brake 0.5 Nm

Encoder



DCmind: DC DIRECT-DRIVE BRUSH MOTORS

Ø 63 mm - 209 W



- > Silent motor
- > 24 V built in EMC filter class B
- > Excellent efficiency
- > Long life
- > IP65
- > In accordance with UL - CE - ROHS regulations

Part numbers

	24 V	48 V	90 V	120 V
Type	89890	89890	89890	89890
Voltage	24 V ^{VDC}	48 V ^{VDC}	90 V ^{VDC}	120 V ^{VDC}
References	89890011 89890511 89890911	89890003 89890503 89890903	89890004 89890504 89890904	89890005 89890505 89890905
Option: IP65 level				
Option: holding brake 0.5 Nm, 24 V ^{VDC}				
Option: 2 channels encoder 1000 pulses/revolution, 5 V ^{VDC}				
No-load characteristics	4000	3700	3410	3430
Speed (rpm)	179	207	218	207
Absorbed current (A)	0.34	0.16	0.09	0.07
Nominal characteristics				
Speed (rpm)	3430	3370	3320	3350
Torque (mNm)	290	290	290	290
Output power (W)	104	102	101	102
Absorbed current (A)	5.4	2.53	1.34	1.01
Efficiency (%)	80	84	84	84
Maximum efficiency characteristics				
Speed (rpm)	3660	3480	3410	3430
Torque (mNm)	179	207	218	207
Output power (W)	69	75	78	83
Absorbed current (A)	3.5	1.9	1	0.82
Efficiency (%)	82	84	84	84
General characteristics	Class E	Class E	Class E	Class E
Insulation conforming to IEC60085	Class E	Class E	Class E	Class E
Noise level (dBA)	35	35	35	35
Max. output power (W)	209	269	269	281
Starting torque (mNm)	2000	2680	2780	2875
Starting current (A)	35.3	22.2	12.1	9.4
Resistance (Ω)	0.73	2.2	7.4	12.8
Inductance (mH)	57	3.3	12	21
Torque constant (mNm/A)	1.1	1.5	1.6	1.6
Electrical time constant (ms)	13	9	9	9
Mechanical time constant (ms)	650	650	650	650
Inertia (g.cm ²)	1600	1600	1600	1600
Weight (g)	12	12	12	12
Commutator segments	5000	5000	5000	5000
Service life (h)	200	200	200	200
Wires length (mm)	✓	✓	✓	✓
Ball bearing	✓	✓	✓	✓
Comments	IP65 level except for the output shaft. Encoder and brake options are IP20.			

Product adaptations, contact us




- > Special output shaft
- > Shaft with pinion, pulley, worm gear
- > Special supply voltage
- > Other wire length
- > Optical or Hall effect encoder - 1 or 2 channels
- > Specific motor mounting flange
- > Special motor connectors
- > IP67, IP69K


Product made to order

Curves


89890011 - 89890511 - 89890911




89890003 - 89890503 - 89890903



89890004 - 89890504 - 89890904




89890005 - 89890505 - 89890905



- Speed (rpm)
- Current (A)
- Torque at nominal
- Torque at maximum efficiency


Dimensions (mm)



- 4 x M5 at 90° depth 10 over Ø 40
- 4 x Ø 3.65 at 90° depth 8 over Ø 48
- 4 x M5 at 90° depth 7 over Ø 40

Options




Holding brake 0.5 Nm



GEARBOXES FOR DCmind BRUSH RANGE

3 to 25 Nm

- > Planetary and worm gearboxes, very silent versions
- > Shafts on ball bearings
- > Long service life




Part numbers

Family	A1	B1	RAD10
Type of gearbox	Planetary ϕ 42	Planetary ϕ 52	Worm gear
Associated motors			
Gear motor reference	8981 A1 / A5 / A9		
8980 IP85 / Holding brake / Encoder			
8950 IP85 / Holding brake / Encoder			
89830 IP85 / Holding brake / Encoder			
89830 IP85 / Holding brake / Encoder			
General characteristics			
Number of stages	1 2 3	1 2 3	1
Maximum permitted torque (Nm)	3 7.5 15	4 12 25	10
Efficiency	0,8 0,75 0,7	0,8 0,75 0,7	0,6 → 0,3
Axial dynamic load (daN)	5 8 11	6 10 15	10
Radial dynamic load (daN)	16 23 30	20 32 45	15
Weight (kg)	0,3 0,4 0,5	0,7 0,9 1,1	0,6
Standard reduction ratios	9 45 302	7-9 28-45 302	5 - 10 - 20 - 30 - 50
Other ratios possible	58 - 137 - 232 - 393	58 - 137 - 192 - 232 - 393	15 - 100
Operating temperature	-30 → +70°C	-30 → +70°C	-10 → +75°C
Typical noise level	45 dBA	45 dBA	45 dBA
Comments			
Planetary gearboxes:			
To maintain a very low noise level, the motor pinion is precision machined on motor shaft to obtain optimum concentricity and parallelism. The gears in the first stage are helical-cut and made from a composite material. This design significantly improves gear life by reducing wear due to friction, increases gearbox efficiency and ensures a very low noise level even with the gearbox under load.			
Worm gearbox:			
This gearbox combines a tempered steel worm gear with a hardened bronze helical wheel, a combination that ensures a long service life. The helical wheel rotates in a grease reservoir to provide an excellent slip coefficient and dissipate heat. O-rings and lip seals equipped with garter springs are used to ensure sealing the gearbox output shaft. The gearbox casing is made of aluminium to maximize heat dissipation. However, because of the high power rating of this gearbox and the lower efficiency inherent in ratio worm gearboxes, care must be taken not to exceed a temperature of 75°C on the gearbox casing during operation. The output shaft configuration can be right, left, or a dual shaft (shaft output on both sides).			


Dimensions (mm)

Planetary gearbox ϕ 42 type A1




- 1 Parallel key 3 x 3 x 16 DIN6885
 - 2 M3, depth 9
 - 3 4 x M3 at 90°, depth 7 over ϕ 32
 - 4 4 x M4 at 90°, depth 10 over ϕ 36
- L1 1 stage: 48,5 max.
L1 2 stages: 61,6 max.
L1 3 stages: 74,7 max.

Planetary gearbox ϕ 52 type B1



- 1 Parallel key 4 x 4 x 16 DIN6885
 - 2 M4, depth 10
 - 3 4 x M5 at 90°, depth 10 over ϕ 40
- L1 1 stage: 56,1 max.
L1 2 stages: 70,3 max.
L1 3 stages: 84,5 max.

Worm gearbox RAD10



- 1 Parallel key 4 x 4 x 20 DIN6885
- 2 4 x M4, depth 8 over ϕ 36
- 3 8 x M5, depth 8
- 4 4 x ϕ 3,8 depth 10 over ϕ 40

The left-hand and right-hand sides of the gearbox are identical.

Product adaptations, contact us




- > Special shafts
- > Other reduction ratios
- > Other fixing holes
- > Special mounting flange

DCmind: DC BRUSH GEARMOTORS

Dimensions (mm)

8981A1 - 8980A1 - 8985A1




8981A1
 L 1 stage: 119,9 max.
 L 2 stages: 133 max.
 L 3 stages: 146,1 max.

8980A1
 L 1 stage: 135 max.
 L 2 stages: 148,1 max.
 L 3 stages: 161,2 max.

8985A1
 L 1 stage: 161,1 max.
 L 2 stages: 174,2 max.
 L 3 stages: 187,3 max.

- 1 Parallel key 3 x 3 x 16 DIN6885
- 2 M3, depth 9
- 3 4 x M3 at 90°, depth 7 over Ø 32
- 4 4 x M4 at 90°, depth 10 over Ø 36

8983B1 - 8988B1




8983B1
 L 1 Stage: 159,1 max.
 L 2 Stages: 173,3 max.
 L 3 Stages: 187,5 max.

8988B1
 L 1 stage: 163,6 max.
 L 2 stages: 197,8 max.
 L 3 stages: 212 max.

- 1 Parallel key 4 x 4 x 16 DIN6885
- 2 4 x M5 at 90°, depth 10 over Ø 40
- 3 M4, depth 10

898310 - 898910 (left side shaft output)



898310
 L: 174,2 max.

898910
 L: 198,7 max.

- 1 Parallel key 4 x 4 x 20 DIN6885
- 2 4 x M4, depth 8 over Ø 36
- 3 8 x M5, depth 8
- 4 4 x 3.5, depth 10 over Ø 40

NOTES

AMERICAS**CANADA**

Tel.: +1 (855) 929-5465
americas.custserv@crouzet.com

MEXICO

Tel.: +1 (855) 929-5465
americas.custserv@crouzet.com

USA

+1 (855) 929-5465
americas.custserv@crouzet.com

COUNTRIES NOT LISTED

+1 (855) 929-5465
americas.custserv@crouzet.com

EUROPE / MIDDLE EAST / AFRICA**BELGIUM**

Tel.: +32 (0) 2 620 06 05
Fax: +32 (0) 2 461 00 23
klantenservice@crouzet.com

FRANCE

Tel.: +33 (0) 475 802 101
Fax: +33 (0) 475 828 900
relationclient@crouzet.com

GERMANY / AUSTRIA

Tel.: +49 (0) 2103/9385930
Fax: +49 (0) 2103/980-222
kundenservice@crouzet.com

ITALY

Tel.: +39 (02) 38 594 099
Fax: +39 (02) 82 952 104
assistenzaclienti@crouzet.com

SPAIN / PORTUGAL

Tel.: +34 (91) 215 80 95
Fax: +34 (93) 2 20 02 05
atencionalcliente@crouzet.com

SWITZERLAND

Tel.: +41 (0) 225 67 57 90
Fax: +41 (0) 565 88 02 75
kundenservice@crouzet.com

THE NETHERLANDS

Tel.: +31 (0) 20-654 52 20
klantenservice@crouzet.com

UNITED KINGDOM

Tel.: +44 (0) 2076 600 025
customer.relation@crouzet.com

COUNTRIES NOT LISTED

Tel.: +33 (0) 475 802 102
Fax: +33 (0) 475 828 900
customer.relation@crouzet.com

ASIA / PACIFIC**CHINA**

Tel.: +86 (21) 8025 7166
Fax: +86 (21) 6107 1771
china@crouzet.com

INDIA

Tel.: +91 (80) 4113 2204/05
Fax: +91 (80) 4113 2206
india@crouzet.com

SOUTH KOREA

Tel.: +82 (2) 2679 8312
Fax: +82 (2) 2679 9888
korea@crouzet.com

EAST ASIA PACIFIC

Tel.: +86 (21) 8025 7177
Fax: +86 (21) 6107 1771
eap@crouzet.com

Warning:

The product information contained in this catalogue is given purely as information and does not constitute a representation, warranty or any form of contractual commitment. Crouzet Automatismes SAS and its subsidiaries reserve the right to modify their products without notice. It is imperative that we should be consulted over any particular use or application of our products and it is the responsibility of the buyer to establish, particularly through all the appropriate tests, that the product is suitable for the use or application. Under no circumstances will our warranty apply, nor shall we be held responsible for any application (such as any modification, addition, deletion, use in conjunction with other electrical or electronic components, circuits or assemblies, or any other unsuitable material or substance) which has not been expressly agreed by us prior to the sale of our products.