



-HN: 30µ" GOLD CENTER CONTACT,
100µ" NICKEL OUTER CONTACT
-H: 30µ" GOLD CENTER CONTACT,
3µ'' GOLD OUTER CONTACT
(SEE TABLE 1)

DESIGNED & DIMENSIONED IN MILLIMETERS[INCHES]

TABLE 1				
ITEM	COMPONENT	-HN	-H	
1	SUB ASSEMBLY	SUB-MCX7-P-C-FN-ST-CA3	SUB-MCX7-P-C-F-ST-CA3	
2	PIN	MCX7-P-C-H-ST-CA3-PIN		
3	OUTER FERRULE	MCX-FER-001-N	MCX-FER-001-F	



F:\DWG\MISC\MKTG\MCX7-P-C-XX-ST-CA3-X-MKT.SLDDRW



NOTES:


REVISION L


DO NOT

SCALE FROM

THIS PRINT

- 1. NOTE DELETED. 2. NOTE DELETED.
- 3. NOTE DELETED. 4. NOTE DELETED.
- 5. PRODUCT TO BE PACKAGED PER PRECISION RF SECTION OF PACKAGING MANUAL.
- 6. NOTE DELETED.
- 7. NOTE DELETED.
- 8. NOTE DELETED.





MCX7-P-C-XX-ST-CA3 SHOWN

