


REVISION H








FIG 2 UCC8-010-1-XXX-S-2-A SHOWN (DIFFERENT AS SHOWN, OTHERWISE SAME AS FIG 1) (PPP NOT SHOWN FOR CLARITY) (SEE NOTE 3)




<u>FIG 3</u> UCC8-020-1-XXX-S-1-A SHOWN (DIFFERENT AS SHOWN, OTHERWISE SAME AS FIG 1) (PPP NOT SHOWN FOR CLARITY)

TABLE 2				
No OF POS	"F"	"G"		
-020	7.20 [0.283]	3.55 [0.140]		
-028	10.20 [0.402]	3.35 [0.132]		






0.50±0.25[.020±.010]





0.50±0.25[.020±.010] —







FIG 5 PICK AND PLACE PAD UCC8-020-1-XXX-S-1-A SHOWN (DIFFERENT AS SHOWN, OTHERWISE SAME AS FIG 1)

TABLE 6					
	"H"		"J"		
No OF POS	LEAD STYLE -1		LEAD STYLE -1		
-010	3.63	[0.143]	3.90 [0.154]		
-014	5.13	[0.202]	3.30 [0.134]		
-020	9.00	[0.354]	4.45 [0.175]		
-028	12.00	[0.472]	4.43 [0.173]		



F:\DWG\MISC\MKTG\UCC8-XXX-X-XXX-X-A-XX-MKT.slddrw



USER DIRECTION OF UN-REELING _____

PACKAGING	VIEW
-----------	------



F:\DWG\MISC\MKTG\UCC8-XXX-X-XXX-X-A-XX-MKT.slddrw