NOTES: REVISION AF 1. © REPRESENTS A CRITICAL DIMENSION 2. ALL DIMENSION TO BE SYMMETRICAL ABOUT CENTERLINE DO NOT WITHIN ±.002[.05] UNLESS OTHERWISE STATED. **SCALE FROM** 3. POSITONS -05 THRU -50 ARE TO BE PACKAGED IN TUBES. THIS PRINT 4. MIN CONTACT RETENTION FORCE: 1LB. 5. TAILS TO ARE TO BE SHEARED. MAX BURR, ORIENTED AWAY FROM CUSTOMER'S P.C.B. ONLY, TO BE .0045[.114] 6. MAX CUT FLASH: .015 IN NON-CRITICAL AREAS; NO CUT FLASH TO BE PRESENT IN CRITICAL AREAS AS SHOWN 7. MOLD STEEL CAPABLE OF -02 & -03 POSITION (-A OPTION). BUT NOT ENG'G APPROVED 8. FIRST AND LAST PIN OF EACH ROW TO BE FLUSH TO .003[0.08] BELOW BODY. 9. NOTE DELETED. 10. NOTE DELETED 11. TUBES ARE STANDARD PACKAGING 12. ORDERS WILL BE PACKAGED ACCORDING TO THE SAMTEC PACKAGING EFFICIENCY STANDARDS (SPES) FOUND ON WWW.SAMTEC.COM 13. ATTACH LABEL TO EACH REEL. (EITHER DIRECTION) ПП CLP-XX-DH-X



CLP-1XX-XX-X-DH-X-XX

3µ" FLASH SELECTIVE GOLD IN CONTACT AREA, MATTE TIN ON TAIL


10µ" LÍGHT SELECTIVE GOLD IN CONTACT AREA, MATTE TIN ON TAIL -FM: 3µ" FLASH SELECTIVE GOLD IN CONTACT


AREA, MATTE TIN ON TAIL -LM: 10µ" LÍGHT SELECTIVE GOLD IN CONTACT AREA, MATTE TIN ON TAIL


PACKAGING BLANK: TUBES (SEE NOTE 11) -TR: TAPE AND REEL PACKAGING (SEE NOTE 12 & 13) -FR: FULL REEL QTY. TAPE & REEL (SEE NOTE 12 & 13)

OPTION BLANK: NO ALIGNMENT PINS -A: ALIGNMENT PIN (USE CLP-XX-DH-A BODIES MUST BE MODLED TO POSTION) (AVAILABLE ON POSITIONS -04 THRU -50) (SEE NOTE 7)

BODY SPECIFICATION -DH: DOUBLE HORIZONTAL







PROPRIETARY NOTE UNLESS OTHERWISE SPECIFIED. THIS DOCUMENT CONTAINS CONFIDENTIAL AND DIMENSIONS ARE IN INCHES. PROPRIETARY INFORMATION AND ALL DESIGN MANUFACTURING, REPRODUCTION, USE, PATENT RIGHTS TOLERANCES ARE: AND SALES RIGHTS ARE EXPRESSLY RESERVED BY SAMTEC, INC. THIS DOCUMENT SHALL NOT BE DISCLOSED, IN WHOLE DECIMALS **ANGLES** .XX: ±.01[0.3] .XXX: ±.005[0.13] .XXXX: ±.0020[0.051] OR PART, TO ANY UNAUTHORIZED PERSON OR ENTITY NOR REPRODUCED, TRANSFERRED OR INCORPORATED IN ANY OTHER PROJECT IN ANY MANNER WITHOUT THE EXPRESS WRITTEN CONSENT OF SAMTEC, INC. SHEET SCALE: 4:1

DO NOT SCALE DRAWING

INSULATOR: LCP, UL 94 VO, COLOR: BLACK CONTACT: PHOS BRONZE

PHONE: 812-944-6733 FAX: 812-948-5047 e-Mail info@SAMTEC.com

LOW PROFILE .050 X .050 DOUBLE ROW ASM

520 PARK EAST BLVD, NEW ALBANY, IN 47150


P-1XX-XX-X-DH-X-XX

F:\DWG\MISC\MKTG\CLP-1XX-XX-X-DH-X-XX-MKT.SLDDRW


BY: PURVIS

11-29-1995


SHEET 1 OF 2




-USER DIRECTION OF UNREELING



-TR: TAPE & REEL VIEW (SCALE 2:1)



-DH NO OPTION PT-1-24-02-37 (TUBE USES (2) TP-12)



WITH -A OPTION PT-1-24-01-62 (TUBE USES (2) TP-12)

PACKAGING TUBE VIEW (SCALE 6:1)

PROPRIETARY NOTE

THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION AND ALL DESIGN, MANUFACTURING, REPRODUCTION, USE, PATENT RIGHTS AND SALES RIGHTS ARE EXPRESSLY RESERVED BY SAMTEC, INC. THIS DOCUMENT SHALL NOT BE DISCLOSED, IN WHOLE OR PART, TO ANY UNAUTHORIZED PERSON OR ENTITY NOR REPRODUCED, TRANSFERRED OR INCORPORATED IN ANY OTHER PROJECT IN ANY MANNER WITHOUT THE EXPRESS WRITTEN CONSENT OF SAMTEC, INC.



SHEET SCALE: 4:1

e-Mail info@SAMTEC.com code 55322 LOW PROFILE .050 X .050 DOUBLE ROW ASM

BY: PURVIS

CLP-1XX-XX-X-DH-X-XX

F:\DWG\MISC\MKTG\CLP-1XX-XX-X-DH-X-XX-MKT.SLDDRW

11-29-1995 SHEET 2 OF 2