


<b>PCN Number:</b>	20241025000.0		<b>PCN Date:</b>	October 25, 2024																																		
<b>Title:</b>	Datasheet for XTR105																																					
<b>Customer Contact:</b>	Change Management team	<b>Dept:</b>	Quality Services																																			
<b>Change Type:</b>	Electrical Specification																																					
<b>PCN Details</b>																																						
<b>Description of Change:</b>																																						
<p>Texas Instruments Incorporated is announcing an information only notification. The product datasheet(s) is being updated as summarized below. The following change history provides further details.</p> <div style="display: flex; justify-content: space-between; align-items: center;">  <div style="text-align: right;"> <b>XTR105</b>  <small>SBOS061C – FEBRUARY 1997 – REVISED OCTOBER 2024</small> </div> </div> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Changes from Revision B (August 2004) to Revision C (October 2024)</th> <th style="text-align: right;">Page</th> </tr> </thead> <tbody> <tr> <td>• Added the <i>Pin Configuration and Functions, Specifications, ESD Ratings, Recommended Operating Conditions, Thermal Information, Detailed Description, Overview, Functional Block Diagram, Feature Description, Device Functional Modes, Application and Implementation, Typical Applications, Layout, Layout Guidelines, Device and Documentation Support, and Mechanical, Packaging, and Orderable Information</i> sections.....</td> <td style="text-align: right; vertical-align: bottom;">1</td> </tr> <tr> <td>• Added end equipments in <i>Applications</i> .....</td> <td style="text-align: right; vertical-align: bottom;">1</td> </tr> <tr> <td>• Updated the numbering format for tables, figures, and cross-references throughout the document.....</td> <td style="text-align: right; vertical-align: bottom;">1</td> </tr> <tr> <td>• Added <i>Pin Functions</i> table.....</td> <td style="text-align: right; vertical-align: bottom;">3</td> </tr> <tr> <td>• Moved operating and storage temperature parameters from <i>Electrical Characteristics</i> to <i>Absolute Maximum Ratings</i> .....</td> <td style="text-align: right; vertical-align: bottom;">4</td> </tr> <tr> <td>• Changed minimum operating temperature from -55°C to -40°C in <i>Absolute Maximum Ratings</i> .....</td> <td style="text-align: right; vertical-align: bottom;">4</td> </tr> <tr> <td>• Moved specified temperature and power-supply parameters from <i>Electrical Characteristics</i> to <i>Recommended Operating Conditions</i> .....</td> <td style="text-align: right; vertical-align: bottom;">4</td> </tr> <tr> <td>• Deleted thermal resistance, <math>\theta_{JA}</math> parameters in <i>Electrical Characteristics</i> and replaced with detailed thermal model parameters in <i>Thermal Information</i> .....</td> <td style="text-align: right; vertical-align: bottom;">4</td> </tr> <tr> <td>• Updated formatting of <i>Electrical Characteristics</i> table.....</td> <td style="text-align: right; vertical-align: bottom;">5</td> </tr> <tr> <td>• Changed Voltage accuracy vs temperature typical specification from <math>\pm 0.2\text{mV}/^\circ\text{C}</math> to <math>\pm 0.5\text{mV}/^\circ\text{C}</math> in <i>Electrical Characteristics</i> .....</td> <td style="text-align: right; vertical-align: bottom;">5</td> </tr> <tr> <td>• Updated Figure 5-2, <i>Step Response</i> .....</td> <td style="text-align: right; vertical-align: bottom;">7</td> </tr> <tr> <td>• Updated Figure 5-8, <i>Zero Output and Reference Current Noise vs Frequency</i> .....</td> <td style="text-align: right; vertical-align: bottom;">7</td> </tr> <tr> <td>• Changed description of maximum loop-supply voltage to specified absolute maximum rating in <i>Surge Protection</i> .....</td> <td style="text-align: right; vertical-align: bottom;">14</td> </tr> <tr> <td>• Updated suggested Zener diode part numbers in Figure 6-4, <i>Reverse Voltage Operation and Overvoltage Surge Protection</i> .....</td> <td style="text-align: right; vertical-align: bottom;">14</td> </tr> <tr> <td>• Updated suggested transistor part numbers in Figure 7-1, <i>Basic 2-Wire RTD Temperature Measurement Circuit with Linearization</i> .....</td> <td style="text-align: right; vertical-align: bottom;">15</td> </tr> <tr> <td>• Moved <i>Adjusting Initial Errors</i> into <i>Error Analysis</i> section .....</td> <td style="text-align: right; vertical-align: bottom;">20</td> </tr> </tbody> </table>					Changes from Revision B (August 2004) to Revision C (October 2024)	Page	• Added the <i>Pin Configuration and Functions, Specifications, ESD Ratings, Recommended Operating Conditions, Thermal Information, Detailed Description, Overview, Functional Block Diagram, Feature Description, Device Functional Modes, Application and Implementation, Typical Applications, Layout, Layout Guidelines, Device and Documentation Support, and Mechanical, Packaging, and Orderable Information</i> sections.....	1	• Added end equipments in <i>Applications</i> .....	1	• Updated the numbering format for tables, figures, and cross-references throughout the document.....	1	• Added <i>Pin Functions</i> table.....	3	• Moved operating and storage temperature parameters from <i>Electrical Characteristics</i> to <i>Absolute Maximum Ratings</i> .....	4	• Changed minimum operating temperature from -55°C to -40°C in <i>Absolute Maximum Ratings</i> .....	4	• Moved specified temperature and power-supply parameters from <i>Electrical Characteristics</i> to <i>Recommended Operating Conditions</i> .....	4	• Deleted thermal resistance, $\theta_{JA}$ parameters in <i>Electrical Characteristics</i> and replaced with detailed thermal model parameters in <i>Thermal Information</i> .....	4	• Updated formatting of <i>Electrical Characteristics</i> table.....	5	• Changed Voltage accuracy vs temperature typical specification from $\pm 0.2\text{mV}/^\circ\text{C}$ to $\pm 0.5\text{mV}/^\circ\text{C}$ in <i>Electrical Characteristics</i> .....	5	• Updated Figure 5-2, <i>Step Response</i> .....	7	• Updated Figure 5-8, <i>Zero Output and Reference Current Noise vs Frequency</i> .....	7	• Changed description of maximum loop-supply voltage to specified absolute maximum rating in <i>Surge Protection</i> .....	14	• Updated suggested Zener diode part numbers in Figure 6-4, <i>Reverse Voltage Operation and Overvoltage Surge Protection</i> .....	14	• Updated suggested transistor part numbers in Figure 7-1, <i>Basic 2-Wire RTD Temperature Measurement Circuit with Linearization</i> .....	15	• Moved <i>Adjusting Initial Errors</i> into <i>Error Analysis</i> section .....	20
Changes from Revision B (August 2004) to Revision C (October 2024)	Page																																					
• Added the <i>Pin Configuration and Functions, Specifications, ESD Ratings, Recommended Operating Conditions, Thermal Information, Detailed Description, Overview, Functional Block Diagram, Feature Description, Device Functional Modes, Application and Implementation, Typical Applications, Layout, Layout Guidelines, Device and Documentation Support, and Mechanical, Packaging, and Orderable Information</i> sections.....	1																																					
• Added end equipments in <i>Applications</i> .....	1																																					
• Updated the numbering format for tables, figures, and cross-references throughout the document.....	1																																					
• Added <i>Pin Functions</i> table.....	3																																					
• Moved operating and storage temperature parameters from <i>Electrical Characteristics</i> to <i>Absolute Maximum Ratings</i> .....	4																																					
• Changed minimum operating temperature from -55°C to -40°C in <i>Absolute Maximum Ratings</i> .....	4																																					
• Moved specified temperature and power-supply parameters from <i>Electrical Characteristics</i> to <i>Recommended Operating Conditions</i> .....	4																																					
• Deleted thermal resistance, $\theta_{JA}$ parameters in <i>Electrical Characteristics</i> and replaced with detailed thermal model parameters in <i>Thermal Information</i> .....	4																																					
• Updated formatting of <i>Electrical Characteristics</i> table.....	5																																					
• Changed Voltage accuracy vs temperature typical specification from $\pm 0.2\text{mV}/^\circ\text{C}$ to $\pm 0.5\text{mV}/^\circ\text{C}$ in <i>Electrical Characteristics</i> .....	5																																					
• Updated Figure 5-2, <i>Step Response</i> .....	7																																					
• Updated Figure 5-8, <i>Zero Output and Reference Current Noise vs Frequency</i> .....	7																																					
• Changed description of maximum loop-supply voltage to specified absolute maximum rating in <i>Surge Protection</i> .....	14																																					
• Updated suggested Zener diode part numbers in Figure 6-4, <i>Reverse Voltage Operation and Overvoltage Surge Protection</i> .....	14																																					
• Updated suggested transistor part numbers in Figure 7-1, <i>Basic 2-Wire RTD Temperature Measurement Circuit with Linearization</i> .....	15																																					
• Moved <i>Adjusting Initial Errors</i> into <i>Error Analysis</i> section .....	20																																					
<p>The datasheet number will be changing.</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 33%;">Device Family</td> <td style="width: 33%;">Change From:</td> <td style="width: 33%;">Change To:</td> </tr> <tr> <td>XTR105</td> <td>SBOS061B</td> <td><b>SBOS061C</b></td> </tr> </table>					Device Family	Change From:	Change To:	XTR105	SBOS061B	<b>SBOS061C</b>																												
Device Family	Change From:	Change To:																																				
XTR105	SBOS061B	<b>SBOS061C</b>																																				
<p>These changes may be reviewed at the datasheet links provided.  <a href="http://www.ti.com/product/XTR105">http://www.ti.com/product/XTR105</a></p>																																						
<b>Reason for Change:</b>																																						
To accurately reflect device characteristics. Datasheet update driven by change announced in PCN 20240806000.																																						
<b>Anticipated impact on Fit, Form, Function, Quality or Reliability (positive / negative):</b>																																						

No anticipated impact.			
<b>Changes to product identification resulting from this PCN:</b>			
None.			
<b>Product Affected:</b>			
<b>Devices included in PCN 20240806000</b>			
XTR105UA/2K5			
<b>Datasheet Only</b>			
XTR105P	XTR105PA		

For questions regarding this notice, e-mails can be sent to the Change Management team or your local Field Sales Representative.

### IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES “AS IS” AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements. These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI’s products are provided subject to TI’s Terms of Sale ([www.ti.com/legal/termsofsale.html](http://www.ti.com/legal/termsofsale.html)) or other applicable terms available either on [ti.com](http://ti.com) or provided in conjunction with such TI products. TI’s provision of these resources does not expand or otherwise alter TI’s applicable warranties or warranty disclaimers for TI products.