

Control module, TeSys Giga, 100-250V AC/DC, for LC1G630-800/3P standard version

LX1G3TKUEN

Main

Range	TeSys	
Product or component type	Contactor coil	
Device short name	LX1G	
Poles description	3P	
Range compatibility	TeSys G LX1G contactor coil	
Product compatibility	LC1G630800	
[Uc] control circuit voltage	100250 V AC/DC 50/60 Hz	
Operating time	2035 ms opening 4055 ms closing	
Mechanical durability	5 Mcycles	
Maximum operating rate	600 cyc/mn 60 °C	

Complementary

Coil technology	Built-in bidirectional peak limiting Operational: 0.81.1 Uc (at 60 °C) Drop-out: 00.45 Uc (at 60 °C)	
Control circuit voltage limits		
Connections - terminals	Control circuit: push-in termination 1 cable(s) 0.22.5 mm² solid stranded without cable end sleeve AWG 26AWG 12 Control circuit: push-in termination 1 cable(s) 0.252.5 mm² flexible with cable end sleeve AWG 24AWG 14 Control circuit: push-in termination 2 cable(s) 0.51.0 mm² rigid or stranded with cable end sleeve AWG 20AWG 18	

Environment

IP degree of protection	3000 m without derating 5000 m with derating factor	
Operating altitude		
Electromagnetic compatibility	EMC immunity conforming to IEC 60947-4-1 Emission tests criteria A conforming to IEC 60947-4-1 Immunity to radiated radio-electrical interference - test level: 20 V/m conforming to EN/IEC 61000-4-3 Voltage dips and interruptions immunity test conforming to SEMI F47	
Standards	EN/IEC 60947-4-1 UL 60947-4-1A CSA C22.2 No 60947-4-1	
Pollution degree	3 conforming to IEC 60947-1	
ambient air temperature for operation	-2560 °C	
Ambient air temperature for storage	-6080 °C	

Permissible ambient air temperature around the device	-4070 °C at Uc	
Height	130 mm	
Width	192 mm	
Depth	211 mm	
Product weight	2145 g	
Quantity per set	1	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	22 cm
Package 1 Width	27 cm
Package 1 Length	29 cm
Package 1 Weight	2.5 kg



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Environmental Disclosure

Product Environmental Profile

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	6fbdad13-bb7c-47d4-a6d6-d82dd6f54349
China RoHS Regulation	China RoHS declaration
PVC free	Yes

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Halogen content performance	Halogen free plastic parts product
Take-back	No

Product datasheet

LX1G3TKUEN

Installation

Installation Videos

TeSys Giga - How to replace control module