

Photovoltaic panel switch-off - SCK-RSD-100 - 2905029

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Photovoltaic panel shutdown, SOLARCHECK RSD shutdown unit for safe isolation of PV panels from the string group.

Product Description

Intelligent photovoltaic panel shutdown with Auto Rapid Shutdown:

Based on the analysis of current and voltage conditions in the string lines and in the individual panels, the SOLARCHECK RSD system shutdown units are able to distinguish between the various operating states. In accordance with the fail-safe principle, any deviation from a normal operating state leads to a shutdown, regardless of whether the inverter is shut down, a string line or panel is defective, etc. The intelligent startup unit automatically puts the system back into operation when a safe and technically faultless system environment is present. SOLARCHECK RSD tracks the operating state of the inverter. The system can therefore easily be manually switched on and off via the inverter, for maintenance purposes, for example. This technology, developed and patented by Phoenix Contact, is more reliable and faster than any human assessment or manual intervention.

Why buy this product

- Safety as a result of patented error detection and safe photovoltaic panel shutdown
- Controlled restart via safe autostart
- No additional communication required, either wirelessly or via cables
- Easy to install in new and existing systems using existing DC cables
- Easy startup without any programming or manual setup



Key Commercial Data

Packing unit	1 STK
Custom tariff number	85371099
Country of origin	Germany

Technical data

System connection

Input voltage range	20 V DC ... 50 V DC
Power dissipation	< 1.5 W

Photovoltaic panel switch-off - SCK-RSD-100 - 2905029

Technical data

System connection

Number of PV panels that can be connected	1
Cable type	PV cable
Conductor cross section	4 mm ² (System connection)
Cable length	150 mm (System connection)
	800 mm (System connection)
Connection method	PV connector
Release	via SCK-RSD-400 / SCK-RSD-600 start unit

General

Rated surge voltage	12 kV
Degree of protection	IP65/IP67
Overvoltage category	III
Degree of pollution	3
Mounting type	Mounting screws

Dimensions

Width	119 mm
Height	118 mm
Depth	35 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Altitude	≤ 4000 m
Permissible humidity (operation)	10 % ... 95 %

Standards and Regulations

Electromagnetic compatibility	Conformance with EMC directive
Standards/regulations	EN 61010
	EN 50548 +A1:2013 +A2:2014

Classifications

eCl@ss

eCl@ss 5.1	27210902
eCl@ss 6.0	27210902
eCl@ss 8.0	27210123
eCl@ss 9.0	27210123

Photovoltaic panel switch-off - SCK-RSD-100 - 2905029

Classifications

ETIM

ETIM 5.0	EC002475
----------	----------