

Triple-deck terminal block; Through/through/through terminal block; L/L/L; gray housing

Note: Some items may not be available from your local WAGO company.
Please note that the quantities ordered in the shopping cart are rounded up to the PU (SPU).

RoHS ☒ Compliant



Description

Remarks

Item properties

Miscellaneous		
Name	Value	Unit
Safety information 1	Max. insulation diameter: 4.4mm	
Packaging type	BOX	
Rating no.	IECEN 60947-1-1	
Rated voltage (III / IV)	500	V
Rated impulse voltage (III / IV)	6	kV
Rated current [A]	(II / 3) : Over-voltage category III / Pollution degree 3	A
Legend (ratings)		
Type of wiring	Front-entry wiring	
Total number of connection points	6	
Total number of potentials	3	
Number of levels	3	
Connection technology	CAGE CLAMP®	
Actuation type	Operating loop	
Connectable conductor materials	Copper	
Solid conductor	0.08 ... 2.5 mm ² / 18 ... 12 AWG	
Fine-stranded conductor	0.08 ... 4 mm ² / 18 ... 12 AWG	
Strip length	6 ... 7 mm / 0.24 ... 0.28 Inch	
Width	5 mm / 0.197 Inch	
Width from upper-edge of DIN-35 rail	52.5 mm / 2.069 Inch	
Depth	106 mm / 4.173 Inch	
Design	horizontal	
Type of mounting	Carrier rail 35 x 15	
Potential marking	L,LL	
Marking level	Color marking	
Color	gray	
Fine fault [mΩ]	0.278	mΩ
Weight [kg]	17.352	g
Main product function	Multilevel terminal blocks	
Product type	Through rail-mount term. blocks	