

Twinaxial cable RG_22_B/U

Description

RG: RG type RF cables

RG22 twinax, 95 Ohm, 1 GHz, 85°C, ø10.8 mm, PVC jacket



Technical Data

Construction

	Material	Detail	Diameter
1 st Centre conductor	Copper	Strand-07	1.2 mm
1 st Dielectric	PE (Polyethylene)		2.25 mm
2 nd Centre conductor	Copper, Tin plated	Strand-07	1.2 mm
2 nd Dielectric	PE (Polyethylene)		2.25 mm
Dielectric	PE (Polyethylene)		typ. 7.25
Outer conductor	Copper, Tin plated	Braid, 94%	8 mm
Outer Conductor	Copper, Tin plated	Braid, 95 %	8.7 mm
Jacket	PVC II (low migration)	RAL 9005 - bk	10.8 mm +/- 0.15

Print: HUBER+SUHNER RG 22 B/U 95 Ohm (production order number)

Electrical Data

Impedance	95 Ω +/- 5
Max. operating frequency	1 GHz
Capacitance	53 pF/m
Velocity of signal propagation	66 %
Signal delay	5 ns/m
Insulation resistance	≥ 1 x 10 ⁸ MΩm
Max. operating voltage	1 kV _{rms} (at sea level)
Test voltage	2 kV _{rms} (50 Hz/1 min)

Mechanical Data

Weight		17.6 kg/100 m
Min. bending radius	static	55 mm
	repeating (for max. 50 bendings)	110 mm
	dynamic	220 mm

Environmental Data

Temperature range	-25 °C to +85 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Additional Information

MIL reference: M17/182-00001 (former reference: M17/15-RG022)

Ordering Information

Order as RG_22_B/U

Remarks

(For details refer to the HUBER+SUHNER RF CABLES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

Twinaxial cable
RG_22_B/U

Suitable Connectors

Cable group U99 Customer Specific