




8700 E. Thomas Road  
Scottsdale, AZ 85251  
Tel: (602) 941-6300  
Fax: (602) 947-1503

**SMDA03C-4-2**  
thru  
**SMDA24C-4-2**  
*TVSarray' Series*

#### DESCRIPTION (300 watt)

This TRANSIENT VOLTAGE SUPPRESSOR (TVS) array is packaged in a SO-8 configuration giving protection to 4 Bidirectional data or interface lines. It is designed for use in applications where protection is required at the board level from voltage transients caused by electrostatic discharge (ESD) as defined in IEC 1000-4-2, electrical fast transients (EFT) per IEC 1000-4-4 and effects of secondary lighting.



These TVS arrays have a peak power rating of 300 watts for an 8/20μsec pulse. This array is suitable for protection of sensitive circuitry consisting of TTL, CMOS DRAM's, SRAM's, HCMOS, HSIC microprocessors, and I/O transceivers. The SMDAXXC-4-2 product provides board level protection from static electricity and other induced voltage surges that can damage sensitive circuitry.

#### FEATURES

- Protects up to 4 Bidirectional lines
- Surge protection Per IEC 1000-4-2, 1000-4-4
- SO-8 Packaging

#### MECHANICAL

- Molded SO-8 Surface Mount
- Weight: 1.5 grams (approximate)
- Marking: Logo, device number, date code
- Pin #1 defined by DOT on top of package

#### MAXIMUM RATINGS

- Operating Temperatures: -55°C to +150°C
- Storage Temperature: -55°C to +150°C
- Peak Pulse Power: 300 Watts (8/20 μsec, Figure 1)
- Pulse Repetition Rate: <.01%

#### PACKAGING

- Tape & Reel EIA Standard 481-1-A
- 13 inch reel 2,500 pieces (OPTIONAL)
- Carrier tubes 95 pcs per (STANDARD)

#### ELECTRICAL CHARACTERISTICS PER LINE

Characteristics @ 25°C Unless otherwise specified

Part Numbers	Device Marking	Stand off voltage V <sub>WM</sub> Volts	Breakdown voltage V <sub>BR</sub> @ V <sub>BR</sub> =1mA Volts	Clamping voltage V <sub>C</sub> @ 1Amp (Figure 2) Volts	Clamping voltage V <sub>C</sub> @ 5Amp (Figure 2) Volts	Leakage current I <sub>D</sub> @ V <sub>WM</sub> μAmps	Capacitance (f=1 MHz) C @ 0V pF	Temperature Coefficient of V <sub>BR</sub> α <sub>VBR</sub> mV/°C
		MAX	MIN	MAX	MAX	MAX	TYP	MAX
SMDA03C-4-2	RFA	3.3	4	6.5	7.5	25	300	-5
SMDA05C-4-2	RFB	5	6.0	9.8	11	10	200	3
SMDA12C-4-2	RFC	12	13.3	19	24	1	75	10
SMDA15C-4-2	RFD	15	16.7	24	30	1	50	13
SMDA24C-4-2	RFE	24	26.7	43	55	1	35	30

NOTE: TVS product is normally selected based on its stand off Voltage V<sub>WM</sub>. Product selected voltage should be equal to or greater than the continuous peak operating voltage of the circuit to be protected.

Application: The SMDAXXC-4-2 product is designed for transient voltage suppression protection of ESD sensitive components at the board level. It is an ideal product to be used for protection of I/O Transceivers.

WAVE FORMS




FIGURE 1  
Peak Pulse Power Vs Pulse Time






FIGURE 2  
Pulse Wave Form


MOUNTING PAD SO-8



CIRCUIT DIAGRAM



SO-8 PACKAGE



DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.188	0.197	4.77	5.00
B	0.150	0.158	3.81	4.01
C	0.053	0.069	1.35	1.75
D	0.011	0.021	0.28	0.53
F	0.016	0.050	0.41	1.27
G	0.050 BSC		1.27 BSC	
J	0.006	0.010	0.15	0.25
K	0.004	0.008	0.10	0.20
L	0.189	0.206	4.80	5.23
P	0.228	0.244	5.79	6.19