

WE310G4

Wi-Fi 802.11 a/b/g/n

Bluetooth® LE



Product Description

The WE310G4 is a fully integrated, dual-band (2.4/5 GHz), combination Wi-Fi 4 and Bluetooth® LE (qualified against Bluetooth® Core 5.4) module. It provides an easy, cost-effective way for manufacturers to add wireless connectivity to their products. The module is based on an integrated dual-core system on chip, composed by:

- A high-performance application processor (running on ARM® Cortex®-M33)
- A low-power MCU (ARM Cortex-M23) for Wi-Fi and Bluetooth® Low Energy

The module also integrates 4MB of internal flash with wide array of peripherals (SDIO, SPI, UART, ADC, PWM, GPIO, I2S, I2C, USB). The WE310G4 provides a low-cost, high-speed serial-to-Wi-Fi/Bluetooth® Low Energy connection to an embedded design built on an 8/16/32-bit microcontroller through UART, SPI or SDIO interfaces. Furthermore, the module can be implemented as a hostless (stand-alone) solution. It offers up to 456 Kb of SRAM dedicated to customer application development.

The WE310G4 is ideal for organizations with limited Wi-Fi/Bluetooth® Low Energy or RF expertise or those seeking a faster time to market. It reduces RF design time and removes testing and certification burdens. The module is IEEE 802.11 a/b/g/n and Bluetooth certified and complies with Wi-Fi Alliance and BT SIG-v5 requirements.

The module is self-contained with full Wi-Fi, BLE and TCP/IP networking stacks. It supports a complete security feature suite with modes that include (among others):

- Secure Boot
- TrustZone-M
- WPA3 Personal and Enterprise
- Upper-layer security protocols (e.g., TLS-1.3/SSL and HTTPS)

The module can be set up (provisioning) from a smartphone or laptop through the innovative Limited AP mode or Bluetooth® Low Energy. The WE310G4 module is easily designed into embedded systems. It allows customers to develop devices and appliances that connect to other local devices or the internet over Wi-Fi. Finally, the WE310G4 is pin-to-pin compatible with the Telit Cinterion WE310F5 (single-band module alternative). This compatibility guarantees effortless hardware and software migration.

Key Features

- Dual-band Wi-Fi 4 and Bluetooth® LE (qualified against Bluetooth® Core 5.4)
- Ease of system integration, pin-to-pin compatible with WE310F5 (single-band module alternative)
- Low power consumption
- Serial-to-Wi-Fi hosted implementation
- Telit IoT AppZone IDE for hostless customer application development
- Wide range of peripherals (including UART, SPI and SDIO)
- Advanced security features (including WPA3) with integrated crypto hardware
- Industrial-grade temperature range (-40 °C to +85 °C)
- Variants with (WE310G4-I) and without (WE310G4-P) antenna
- Certified modules

AVAILABLE FOR

North America

EMEA

Japan*

Korea**

*Started/**Planned



Target Applications

Smart Home

- Home automation
- Home appliances
- Home security and alarm
- IP cameras/speakers
- Smart lighting

Health Care & Medical

- Remote Patient Monitoring
- Healthcare Devices
- Wellness Devices
- Pet/Animal Trackers
- Medical Wearables

Industrial and commercial

- Industrial automation
- Energy management
- Robotics
- Building automation
- Smart city

Others Applications

- Aftermarket OEM telematics
- Fleet management
- Smart parking
- Printers
- Asset management

WE310G4

Wireless Specification	Wi-Fi - 802.11 a/b/g/n (2.4 GHz, 5 GHz) Bluetooth® LE (qualified against Bluetooth® Core 5.4)	
Solution Architecture	Hosted IoT module (AT command) or Standalone (hostless)	
Host Interface	UART, SPI, SDIO	
Other Interface	I2C, ADC (12-bit), DAC, I2S, SWD, USB, GPIOs	
Wi-Fi Modes	AP (Access Point) 4 STA (clients) Concurrent Mode (AP + STA) WPA3*/WPA2 Enterprise* - Personal	
BLE Modes	Central Peripheral Concurrent	
Security Features	WPA/WPA2 (personal) WPA3 (personal) WPA3 (enterprise) HTTPS server & client TLS-1.2 TLS-1.3	Secure Boot TrustZone HW crypto accelerators Secure eFuse
Coexistence	Built-in Wi-Fi/Bluetooth®	
Provisioning (Through web-apps and native apps)	Bluetooth® Low Energy Enabled Wi-Fi HTTPS Enabled	
Cloud Agent	Amazon AWS IoT Microsoft Azure	
Firmware Upgrade	FOTA	
Dimension	Integrated antenna (WE310G4-I): 18 x 15 mm (LGA package) – WE310F5-I P2P compatible External antenna (WE310G4-P): 14.3 x 13.1 mm (LGA package) – WE310F5-P P2P compatible	
Wi-Fi Tx output power	18 dBm @ 2.4 GHz 19 dBm @ 5.0 GHz	
BLE Tx output power	8 dBm (TBC)	
Internal Flash	4 MB	
Operating Temperature	-40 °C to +85 °C (industrial grade)	
Operating Voltage	3.3 V	
Compliance	FCC/ISED/RED/JATE-JBL***/TELEC-JRL***/KCC** Wi-Fi Alliance, BT SIG	
Environmental Compliance	RoHS, REACH	

*Not supported in AP mode
**Planned
***Started

QUESTIONS? VISIT WWW.TELIT.COM/CONTACT-US

 Like Us on Facebook  Follow Us on LinkedIn  Follow Us on X  Subscribe to Our Channel