

FPA2K

Thick Film Power Resistor

For variable speed drivers, power supplies, control devices, robotics, motor control and other power designs. The easy mounting fixture guarantees an auto calibrated pressure to the cooling plate of approx 300 N

FEATURES


- 2000 Watt operating power
- Non- Inductive Design
- High insulation and partial discharge performance
- Materials in accordance with UL94-V0
- RoHS Compliant



CHARACTERISTICS

Resistance values	1R to 6K
Resistance tolerance	J (5%) and K (10%)
Temperature coefficient	±150ppm/°C - others available on request, measured +25°C to +85°C
Maximum working voltage	5kVdc - others available on request not exceeding maximum power
Short time overload	2400W at 70°C for 10 sec $\Delta R = 0.4\%$ max
Power rating	2000W at 125°C bottom case temperature resp. 60°C heat sink temp
Maximum continous current	120 A
Electric strength voltage	7kVrms/50Hz/500VA , test time 1 min between case and terminal
Single shot voltage	up to 12kV normwave (1.5/50 μ sec)
Partial discharge	4kVrms < 10pC
Insulation resistance	10G Ω min at 1000V
Creepage distance	>42mm min
Air distance	>14mm min
Inductance	≥80nH typical, measuring frequency 10kHz
Capacity/Mass	≥120pF typical, measuring frequency 10kHz
Capapcity/Parallel	≥40pF typical, measuring frequency 10kHz
Operating temperature	-55°C to +150°C
Max torque for contacts	1.8 Nm to 2Nm
Max torque for mounting	1.6Nm to 1.8 Nm M4 screws
Weight	~120 g

DERATING CURVE




Derating (thermal resist.)FPA2K: 66.6 W/K (0.015K/W). Power Rating:2000 W at 125°C bottom case temperture. Best results can be reached by using a thermal conduction to the heatsink $R_{th-cs} < 0.025^{\circ}\text{K/W}$, which can be reached by using thermal transfer compound with a head conductivity of 1W/mK The flatness of the cooling plate must be better than 0.05mm overall. The roughness of the surface should not exceed 6.4 μ m

TEST SPECIFICATIONS

Test	Method	Tolerance Drift
Short time overload	2400 W/10 sec	0.40%
Humidity steady state	56 days/40°C/95%	0.25%
Temp. Cycling	-55/+125/5cycles	0.20%
Shock	40g/4000 times	0.25%
Vibrations	2-500Hz/10g	0.25%
Load life 3,000 cyl	PN 30 min on/ 30 min off	0.40%
Terminal strengths	200N for hexa. thread contacts	0.05%

DIMENSIONS

(mm)




Standard Terminals

Air distance: 14mm [0.5512] min.
 Creeping distance: 42mm [1.6535] min.

Terminal height 30/32
 Standard

Terminal height 25/25
 Optional



GENERAL SPECIFICATIONS

Electric support -Alumina ceramic metalized with ALTOX film on the bottom for improved heat transfer and optimum discharge

Encapsulation -Resin-filled epoxy casing with large creepage distance to mass, large strike distance between the terminals and high insulation resistance(CTI 600)

Resistance Element -Special design for low inductance and capacitance values. The element employs our special METOXFILM, which demonstrates stability whilst covering high wattage and pulse loading.

ORDERING INFORMATION

Standard Resistor:

Series, Resistance Value, Tolerance, Connector height
 e.g:

FPA2K 10R J 30/32 mm