

1. Product profile

1.1 General description

400 W GaN packaged asymmetric Doherty power transistor for base station applications at frequencies from 2300 MHz to 2700 MHz.

Table 1. Typical performance

Typical RF performance at $T_{case} = 25\text{ °C}$ in an asymmetrical Doherty application demo circuit.
 $V_{DS} = 50\text{ V}$; $I_{Dq} = 200\text{ mA}$ (main); $V_{GS(amp)peak} = -4.3\text{ V}$; unless otherwise specified.

Test signal	f (MHz)	I_{Dq} (mA)	V_{DS} (V)	$P_{L(AV)}$ (dBm)	G_p (dB)	η_D (%)	ACPR (dBc)	$P_{L(5dB)}$ (dBm)
1-carrier W-CDMA [1]	2496 to 2690	200	50	47.2	15.4	53.7	-27.0	-
pulsed CW [2]	2496 to 2690	200	50	-	-	-	-	55.8

[1] Test signal: 1-carrier W-CDMA; 3GPP test model 1; 64 DPCH; PAR = 10.5 dB at 0.01 % probability on CCDF.

[2] Test signal: pulsed CW; $t_p = 30\text{ }\mu\text{s}$; $\delta = 35\text{ }\%$.

Table 2. Typical performance

Typical RF performance at $T_{case} = 25\text{ °C}$ in an asymmetrical Doherty application demo circuit.
 $V_{DS} = 50\text{ V}$; $I_{Dq} = 270\text{ mA}$ (main); $V_{GS(amp)peak} = -5.2\text{ V}$; unless otherwise specified.

Test signal	f (MHz)	I_{Dq} (mA)	V_{DS} (V)	$P_{L(AV)}$ (dBm)	G_p (dB)	η_D (%)	ACPR (dBc)	$P_{L(5dB)}$ (dBm)
1-carrier W-CDMA [1]	2300 to 2400	270	50	47.2	14.7	51.5	-23.9	-
pulsed CW [2]	2300 to 2400	270	50	-	-	-	-	55.7

[1] Test signal: 1-carrier W-CDMA; 3GPP test model 1; 64 DPCH; PAR = 10.5 dB at 0.01 % probability on CCDF.

[2] Test signal: pulsed CW; $t_p = 30\text{ }\mu\text{s}$; $\delta = 35\text{ }\%$.

1.2 Features and benefits



- Excellent digital pre-distortion capability
- High efficiency
- Designed for broadband operation
- Lower output capacitance for improved performance in Doherty applications
- Internally matched for ease of use
- For RoHS compliance see the product details on the Ampleon website

1.3 Applications

- RF power amplifier for base stations and multi carrier applications in the 2300 MHz to 2700 MHz frequency range

2. Pinning information

Table 3. Pinning

Pin	Description	Simplified outline	Graphic symbol
1	drain1 (main)		
2	drain2 (peak)		
3	gate1 (main)		
4	gate2 (peak)		
5	video decoupling (main)		
6	video decoupling (peak)		
7	source ^[1]		

[1] Connected to flange.

3. Ordering information

Table 4. Ordering information

Package name	Orderable part number	12NC	Packing description	Min. orderable quantity (pieces)
SOT1275-1	C4H27W400AVZ	9349 604 85517	Tray; 20-fold; dry pack	60
	C4H27W400AVY	9349 604 85518	TR13; 100-fold; 44 mm; dry pack	100

4. Limiting values

Table 5. Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134).

Symbol	Parameter	Conditions	Min	Max	Unit
V_{DD}	supply voltage	operating	-	52	V
V_{DS}	drain-source voltage	$V_{GS} = -8$ V	-	150	V
$V_{GS(amp)main}$	main amplifier gate-source voltage		-15	+2	V
$V_{GS(amp)peak}$	peak amplifier gate-source voltage		-15	+2	V
$I_{GF(amp)main}$	main amplifier forward gate current		-	21.6	mA
$I_{GF(amp)peak}$	peak amplifier forward gate current		-	35.1	mA
T_{stg}	storage temperature		-65	+150	°C
T_{ch}	active die channel temperature	^[1]	-	275	°C
T_{case}	case temperature	operating ^[1]	-40	+130	°C

[1] Continuous use at maximum temperature will affect the reliability, for details refer to the online MTF calculator.

5. Thermal characteristics

Table 6. Thermal characteristics

Symbol	Parameter	Conditions	Typ	Unit
$R_{th(s-c)(IR)}$ [1][3]	thermal resistance from active die surface to case by Infrared measurement	$V_{DS} = 48 \text{ V}$; $I_{Dq} = 300 \text{ mA}$; $V_{GS(amp)peak} = -4.8 \text{ V}$; $T_{case} = 80 \text{ }^{\circ}\text{C}$; CW; $P_L = 55 \text{ W}$; $P_{dis} = 60 \text{ W}$	0.84	K/W
$R_{th(ch-c)(FEA)}$ [2][3][4]	thermal resistance from active die channel to case by Finite Element Analysis	$T_{case} = 80 \text{ }^{\circ}\text{C}$; $P_{dis} = 59 \text{ W}$	1.40	K/W

[1] Infrared (IR) thermal values are for reference only and cannot be used to determine performance or reliability.

[2] Finite Element Analysis (FEA) thermal values have been used for the online MTF calculator.

[3] P_{dis} is total Doherty dissipation power which includes main and peak amplifier.

[4] Peak amplifier is actually contributing to 15.3 % Doherty dissipation power.

6. Characteristics

Table 7. DC characteristics

$T_j = 25 \text{ }^{\circ}\text{C}$ unless otherwise specified.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Main device						
$V_{GS(th)}$	gate-source threshold voltage	$V_{DS} = 10 \text{ V}$; $I_D = 21.6 \text{ mA}$	-3.10	-2.70	-2.30	V
V_{GSq}	gate-source quiescent voltage	$V_{DS} = 50 \text{ V}$; $I_D = 432 \text{ mA}$	-3.01	-2.61	-2.21	V
$I_{D(leak)}$	drain leakage current	$V_{GS} = -10 \text{ V}$; $V_{DS} = 50 \text{ V}$	-	-	5.23	mA
I_{GSS}	gate leakage current	$V_{GS} = -8 \text{ V}$; $V_{DS} = 0 \text{ V}$	-	-	1.05	mA
Peak device						
$V_{GS(th)}$	gate-source threshold voltage	$V_{DS} = 10 \text{ V}$; $I_D = 35.1 \text{ mA}$	-3.16	-2.76	-2.36	V
V_{GSq}	gate-source quiescent voltage	$V_{DS} = 50 \text{ V}$; $I_D = 702 \text{ mA}$	-3.05	-2.65	-2.25	V
$I_{D(leak)}$	drain leakage current	$V_{GS} = -10 \text{ V}$; $V_{DS} = 50 \text{ V}$	-	-	8.49	mA
I_{GSS}	gate leakage current	$V_{GS} = -8 \text{ V}$; $V_{DS} = 0 \text{ V}$	-	-	1.70	mA

Table 8. RF characteristics

Test signal: 1-carrier W-CDMA; PAR = 7.2 dB at 0.01 % probability on the CCDF;
3GPP test model 1; 64 DPCH; $f_1 = 2498.5 \text{ MHz}$; $f_2 = 2687.5 \text{ MHz}$; RF performance at $V_{DS} = 48 \text{ V}$;
 $I_{Dq} = 340 \text{ mA}$; $V_{GS(amp)peak} = -4.6 \text{ V}$ (typical); $T_{case} = 25 \text{ }^{\circ}\text{C}$; unless otherwise specified; in a Doherty production RF test circuit.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
G_p	power gain	$P_{L(AV)} = 50 \text{ W}$	14.0	15.0	-	dB
η_D	drain efficiency	$P_{L(AV)} = 50 \text{ W}$	47.0	51.5	-	%
RL_{in}	input return loss	$P_{L(AV)} = 50 \text{ W}$	-	-12	-8	dB
ACPR	adjacent channel power ratio	$P_{L(AV)} = 50 \text{ W}$	-	-27.0	-24.0	dBc

Table 9. RF characteristics

Test signal: pulsed CW; $t_p = 100 \mu\text{s}$; $\delta = 10 \%$; $f = 2690 \text{ MHz}$; RF performance at $V_{DS} = 48 \text{ V}$; $I_{DQ} = 340 \text{ mA}$; $V_{GS(amp)peak} = -4.6 \text{ V (typical)}$; $T_{case} = 25 \text{ }^\circ\text{C}$; unless otherwise specified; in a Doherty production RF test circuit.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
$P_{L(3dB)}$	output power at 3 dB gain compression	-	200	255	-	W

7. Test information

7.1 Ruggedness in Doherty operation

7.1.1 At $f = 2300 \text{ MHz}$

The C4H27W400AV is capable of withstanding a load mismatch corresponding to $V_{SWR} = 10 : 1$ through all phases under the following conditions: $V_{DS} = 48 \text{ V}$; $I_{DQ} = 300 \text{ mA}$; $V_{GS(amp)peak} = -5.2 \text{ V}$; $P_L = 350 \text{ W}$ (pulsed CW; $t_p = 100 \mu\text{s}$; $\delta = 10 \%$); tested on the Doherty application demo circuit.

7.1.2 At $f = 2500 \text{ MHz}$

The C4H27W400AV is capable of withstanding a load mismatch corresponding to $V_{SWR} = 10 : 1$ through all phases under the following conditions: $V_{DS} = 48 \text{ V}$; $I_{DQ} = 300 \text{ mA}$; $V_{GS(amp)peak} = -4.0 \text{ V}$; $P_L = 260 \text{ W}$ (pulsed CW; $t_p = 100 \mu\text{s}$; $\delta = 10 \%$); tested on the Doherty development RF test circuit.

7.2 Impedance information

Table 10. Typical impedance of main device

Measured load-pull data of main device; all data measured on a harmonic impedance non-optimized load-pull fixture; $I_{DQ} = 400 \text{ mA (main)}$; $V_{DS} = 48 \text{ V}$; test signal: pulsed CW; $t_p = 100 \mu\text{s}$; $\delta = 10 \%$; typical values unless otherwise specified.

f	Z_S [1]	Z_L [1]	P_L [2]	P_L [2]	η_D [2]	G_p [2]
(MHz)	(Ω)	(Ω)	(dBm)	(W)	(%)	(dB)
Maximum power load						
2300	$1.8 - j9.0$	$5.2 - j9.0$	52.8	190	67.5	15.7
2400	$2.2 - j9.9$	$4.9 - j10.8$	52.9	195	66.8	16.1
2500	$3.5 - j10.1$	$3.9 - j10.1$	53.0	199	66.0	16.1
2600	$6.4 - j10.4$	$3.9 - j10.8$	53.0	198	68.9	16.0
2700	$5.4 - j6.5$	$3.6 - j11.3$	52.7	188	65.4	16.3
Maximum drain efficiency load						
2300	$1.8 - j9.0$	$7.9 - j7.6$	51.8	151	73.4	16.9
2400	$2.2 - j9.9$	$6.8 - j6.1$	51.3	133	74.9	17.6
2500	$3.5 - j10.1$	$6.5 - j7.7$	51.4	137	76.8	17.6
2600	$6.4 - j10.4$	$5.6 - j8.0$	51.3	136	77.7	17.0
2700	$5.4 - j6.5$	$4.9 - j9.1$	51.4	138	76.2	18.3

[1] Z_S and Z_L defined in [Figure 1](#).

[2] At 3 dB gain compression.

Table 11. Typical impedance of peak device

Measured load-pull data of peak device; all data measured on a harmonic impedance non-optimized load-pull fixture; $I_{DQ} = 650$ mA (peak); $V_{DS} = 48$ V; test signal: pulsed CW; $t_p = 100$ μ s; $\delta = 10$ %; typical values unless otherwise specified.

f	Z _S [1]	Z _L [1]	P _L [2]	P _L [2]	η_D [2]	G _p [2]
(MHz)	(Ω)	(Ω)	(dBm)	(W)	(%)	(dB)
Maximum power load						
2300	2.8 – j8.0	2.6 – j8.3	55.1	324	62.8	13.3
2400	3.1 – j8.6	2.7 – j8.4	55.4	344	68.1	13.5
2500	3.1 – j9.8	2.6 – j7.6	55.5	354	68.1	13.8
2600	4.9 – j10.0	2.6 – j7.6	55.4	347	70.1	13.5
2700	4.3 – j9.2	2.6 – j8.3	55.1	326	67.2	13.8
Maximum drain efficiency load						
2300	2.8 – j8.0	4.4 – j5.6	53.2	209	71.2	14.6
2400	3.1 – j8.6	3.3 – j6.5	54.3	267	74.5	14.6
2500	3.1 – j9.8	3.4 – j5.8	54.1	259	75.4	14.9
2600	4.9 – j10.0	3.5 – j5.8	53.6	231	74.9	14.3
2700	4.3 – j9.2	3.1 – j6.5	53.6	229	72.5	15.0

[1] Z_S and Z_L defined in [Figure 1](#).

[2] At 3 dB gain compression.




Fig 1. Definition of transistor impedance

7.3 Test circuit

The RF test circuit is used in the 2496 MHz to 2690 MHz frequency range.





Table 12. List of components

See [Figure 2](#) for component layout.


Component	Description	Value	Remarks
C1, C9, C11, C12, C22, C23	multilayer ceramic chip capacitor	10 μF , 100 V	Murata
C3, C4, C5, C7, C10, C18, C19	multilayer ceramic chip capacitor	12 pF	ATC 600F
C6, C25	multilayer ceramic chip capacitor	0.3 pF	ATC 600F
C13, C21	multilayer ceramic chip capacitor	1000 pF	ATC 800B
C14	multilayer ceramic chip capacitor	10 pF	ATC 800B
C15, C20	multilayer ceramic chip capacitor	4.7 μF , 100 V	Murata
C16	multilayer ceramic chip capacitor	2.7 pF	ATC 600F
C17	multilayer ceramic chip capacitor	2.0 pF	ATC 600F
C24	multilayer ceramic chip capacitor	0.1 pF	ATC 600F
C26, C27	multilayer ceramic chip capacitor	1000 μF , 100 V	Murata
R1	resistor	51 Ω	SMD 0603
R2, R3	resistor	10 Ω	SMD 0603
S1, S2	current sensor resistor	10 m Ω	LVK25 SMD1224
X1	coupler		RN2: CMX25Q02

7.4 Graphical data

7.4.1 Pulsed CW




7.4.2 1-Carrier W-CDMA



$V_{DS} = 48$ V; $I_{Dq} = 340$ mA; $V_{GS(amp)peak} = -4.6$ V.

- (1) $f = 2498.5$ MHz
- (2) $f = 2593$ MHz
- (3) $f = 2687.5$ MHz


Fig 4. Power gain and drain efficiency as function of output power; typical values



$V_{DS} = 48$ V; $I_{Dq} = 340$ mA; $V_{GS(amp)peak} = -4.6$ V.

- (1) $f = 2498.5$ MHz
- (2) $f = 2593$ MHz
- (3) $f = 2687.5$ MHz

Fig 5. Adjacent channel power ratio (5 MHz) as a function of output power; typical values




$V_{DS} = 48$ V; $I_{Dq} = 340$ mA; $V_{GS(amp)peak} = -4.6$ V.

- (1) $f = 2498.5$ MHz
- (2) $f = 2593$ MHz
- (3) $f = 2687.5$ MHz

Fig 6. Adjacent channel power ratio (10 MHz) as a function of output power; typical values


7.4.3 2-Tone VBW



8. Package outline

Air cavity plastic earless flanged package; 6 leads

SOT1275-1



Dimensions

Unit	A	b	b ₁	c	D	D ₁	E	E ₁	e	F	H	H ₁	L	Q ⁽¹⁾	U ₁	U ₂	Z	Z ₁	α
max	4.01	3.94	1.14	0.178	20.42	20.37	9.80	9.75		1.14	19.53	12.80	25.40	1.68	20.70	9.91	3.17	5.79	65°
nom									8.89										
min	3.40	3.68	0.89	0.127	20.12	20.17	9.50	9.55		0.94	19.33	12.60	25.20	1.45	20.50	9.70	2.67	5.29	61°

Note

1. Dimension Q is measured 0.1 mm away from the flange.
2. Ringframe and/or ringframe glue shall not overhang at the side of the flange.

sot1275-1_po


Outline version	References				European projection	Issue date
	IEC	JEDEC	JEITA			
SOT1275-1						16-11-15 17-04-13

Fig 8. Package outline SOT1275-1

9. Handling information

CAUTION



This device is sensitive to ElectroStatic Discharge (ESD). Observe precautions for handling electrostatic sensitive devices.

Such precautions are described in the *ANSI/ESD S20.20*, *IEC/ST 61340-5*, *JESD625-A* or equivalent standards.

Table 13. ESD sensitivity

ESD model	Class
Charged Device Model (CDM); According to ANSI/ESDA/JEDEC standard JS-002	C3 [1]
Human Body Model (HBM); According to ANSI/ESDA/JEDEC standard JS-001	1C [2]

[1] CDM classification C3 is granted to any part that passes after exposure to an ESD pulse of 1000 V.

[2] HBM classification 1C is granted to any part that passes after exposure to an ESD pulse of 1000 V.

10. Abbreviations

Table 14. Abbreviations

Acronym	Description
3GPP	3rd Generation Partnership Project
CCDF	Complementary Cumulative Distribution Function
CW	Continuous Wave
DPCH	Dedicated Physical CHannel
GaN	Gallium Nitride
MTF	Median Time to Failure
PAR	Peak-to-Average Ratio
RoHS	Restriction of Hazardous Substances
SMD	Surface Mounted Device
VBW	Video Bandwidth
VSWR	Voltage Standing Wave Ratio
W-CDMA	Wideband Code Division Multiple Access

11. Revision history

Table 15. Revision history

Document ID	Release date	Data sheet status	Change notice	Supersedes
C4H27W400AV v.1	20210924	Product data sheet	-	-

12. Legal information

12.1 Data sheet status

Document status ^{[1][2]}	Product status ^[3]	Definition
Objective [short] data sheet	Development	This document contains data from the objective specification for product development.
Preliminary [short] data sheet	Qualification	This document contains data from the preliminary specification.
Product [short] data sheet	Production	This document contains the product specification.

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL <http://www.ampleon.com>.

12.2 Definitions

Draft — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. Ampleon does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

Short data sheet — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local Ampleon sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

Product specification — The information and data provided in a Product data sheet shall define the specification of the product as agreed between Ampleon and its customer, unless Ampleon and customer have explicitly agreed otherwise in writing. In no event however, shall an agreement be valid in which the Ampleon product is deemed to offer functions and qualities beyond those described in the Product data sheet.

12.3 Disclaimers

Maturity — The information in this document can only be regarded as final once the relevant product(s) has passed the Release Gate in Ampleon's release process. Prior to such release this document should be regarded as a draft version.

Limited warranty and liability — Information in this document is believed to be accurate and reliable. However, Ampleon does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information. Ampleon takes no responsibility for the content in this document if provided by an information source outside of Ampleon.

In no event shall Ampleon be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, Ampleon's aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the *Terms and conditions of commercial sale* of Ampleon.

Right to make changes — Ampleon reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use — Ampleon products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of an Ampleon product can reasonably be expected to result in personal injury, death or severe property or environmental damage. Ampleon and its suppliers accept no liability for inclusion and/or use of Ampleon products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. Ampleon makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using Ampleon products, and Ampleon accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the Ampleon product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

Ampleon does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using Ampleon products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). Ampleon does not accept any liability in this respect.

Limiting values — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) will cause permanent damage to the device. Limiting values are stress ratings only and (proper) operation of the device at these or any other conditions above those given in the Recommended operating conditions section (if present) or the Characteristics sections of this document is not warranted. Constant or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the device.

Terms and conditions of commercial sale — Ampleon products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.ampleon.com/terms>, unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. Ampleon hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of Ampleon products by customer.

No offer to sell or license — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

Non-automotive qualified products — Unless this data sheet expressly states that this specific Ampleon product is automotive qualified, the product is not suitable for automotive use. It is neither qualified nor tested in accordance with automotive testing or application requirements. Ampleon accepts no liability for inclusion and/or use of non-automotive qualified products in automotive equipment or applications.

In the event that customer uses the product for design-in and use in automotive applications to automotive specifications and standards, customer (a) shall use the product without Ampleon's warranty of the product for such

automotive applications, use and specifications, and (b) whenever customer uses the product for automotive applications beyond Ampleon's specifications such use shall be solely at customer's own risk, and (c) customer fully indemnifies Ampleon for any liability, damages or failed product claims resulting from customer design and use of the product for automotive applications beyond Ampleon's standard warranty and Ampleon's product specifications.

Translations — A non-English (translated) version of a document is for reference only. The English version shall prevail in case of any discrepancy between the translated and English versions.

12.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

13. Contact information

For more information, please visit: <http://www.ampleon.com>

For sales office addresses, please visit: <http://www.ampleon.com/sales>

14. Contents

1	Product profile	1
1.1	General description	1
1.2	Features and benefits	1
1.3	Applications	1
2	Pinning information	2
3	Ordering information	2
4	Limiting values	2
5	Thermal characteristics	3
6	Characteristics	3
7	Test information	4
7.1	Ruggedness in Doherty operation	4
7.1.1	At $f = 2300$ MHz	4
7.1.2	At $f = 2500$ MHz	4
7.2	Impedance information	4
7.3	Test circuit	6
7.4	Graphical data	7
7.4.1	Pulsed CW	7
7.4.2	1-Carrier W-CDMA	8
7.4.3	2-Tone VBW	9
8	Package outline	10
9	Handling information	11
10	Abbreviations	11
11	Revision history	11
12	Legal information	12
12.1	Data sheet status	12
12.2	Definitions	12
12.3	Disclaimers	12
12.4	Trademarks	13
13	Contact information	13
14	Contents	14

Please be aware that important notices concerning this document and the product(s) described herein, have been included in section 'Legal information'.

© Ampleon Netherlands B.V. 2021.

All rights reserved.

For more information, please visit: <http://www.ampleon.com>

For sales office addresses, please visit: <http://www.ampleon.com/sales>

Date of release: 24 September 2021

Document identifier: C4H27W400AV