

Flexible low noise cable G_01330_HT-23

Description

G: RF cables with PE dielectrics

Low-noise triax, 50 Ohm, 1 GHz, 85°C, ø4.3 mm, PUR jacket



Technical Data

Construction

	Material	Detail	Diameter
Centre conductor	Copper	Strand-07	0.45 mm
Dielectric	PE (Polyethylene)		1.4 mm
Semi conductor	PVC (Polyvinyl chloride)		1.9 mm
Outer conductor	Copper	Braid, 91 %	2.3 mm
Jacket	PVC (Polyvinyl chloride)	RAL 9005 - bk	2.8 mm +/-
2 nd Screen	Copper	Braid, 90 %	3.3 mm
Outer Jacket	PUR (Polyurethane)	RAL 9005 - bk	4.3 mm +/- 0.2

Print: HUBER+SUHNER G 01330 HT-23 50 Ohm (production order number)

Electrical Data

Impedance	50 Ω
Max. operating Frequency	1 GHz
Capacitance	104 pF/m
Insulation resistance	≥ 1 x 10 ⁶ MΩm
Max. operating voltage	1 kV _{rms} (at sea level)
Test voltage	2 kV _{rms} (50 Hz/1 min)
Max. noise level	10 mV

Mechanical Data

Weight	2.3 kg/100 m
Bending Radius	static 20 mm
	repeated (for max. 50 bendings) 50 mm

Environmental Data

Temperature range	-25 °C... +85 °C
Installation temperature	-20 °C... +60 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Additional Information

Ordering Information

Order as	G_01330_HT-23
----------	---------------

Remarks

(For details refer to the HUBER+SUHNER RF CABLES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

Cable group	U99 Customer Specific
-------------	-----------------------